

Title (en)

Panel to cover walls or ceilings.

Title (de)

Paneel zur Bekleidung von Wänden oder Decken.

Title (fr)

Panneau pour couvrir les murs ou les plafonds.

Publication

EP 0220389 A2 19870506 (DE)

Application

EP 86110166 A 19860724

Priority

DE 3538538 A 19851030

Abstract (en)

1. A panel to cover walls or ceilings of buildings, wherein two parallel longitudinal edges are profiled in such a way that in the position of use a male longitudinal edge engages a female longitudinal edge, the female longitudinal edge having two opposing walls running approximately parallel to the surface of the panel and therewith embracing the upper and lower side of the male longitudinal edge of the neighbouring panel in the position of use and the cross section of the male longitudinal edge tapering towards the front end of the latter, a cavity between the longitudinal edges and the surface of the panel being foamed with an insulating material, characterized in that the female longitudinal edge (2) has in its interior an undercut (4) and the male longitudinal edge (3) has a hook-shaped projection (5) engaging said undercut (4) in the position of use, that the embraced male longitudinal edge (3) recedes relative to the top side (6) thereof and in the position of use a clearance is in each case provided between the front end (12) of the male longitudinal edge (3) and the groove base (13) of the female longitudinal edge (2) as well as between the forward side (14) of the undercut (4) in the direction of insertion and the area (15) of the male longitudinal edge (3) receding relative thereto, the projection (5) engaging behind the undercut (4) within the female longitudinal edge (2) being devised to be approximately hook-shaped in cross section and the hook end (17) of said projection butting against the rear stop face (16) of the undercut (4), while the outside of the hook has a clearance from the groove base (13) of the female longitudinal edge (2) and an area (18) belonging to the male longitudinal edge (3) and forming the back of the hook runs slantwise in cross section to the front end (12) in such a way as to compose the cross sectional taper of the male longitudinal edge (3).

Abstract (de)

Ein Paneel (1) zur Bekleidung von Wänden oder Decken von Bauwerken hat zwei parallele, derart profilierte Längsränder (2 und 3), daß diese in Gebrauchsstellung formschlüssig ineinandereingreifen. Dabei hat ein eine Hinterschneidung (4) aufweisender Aufnahme-Längsrand (2) in Einsteckrichtung vor der Hinterschneidung (4) zwei einander gegenüberliegende, etwa parallel zur Paneeloberfläche (6) verlaufende Wandungen (8 und 9) und umgreift in Gebrauchsstellung damit die Oberseite (10) und die Unterseite (11) des Einsteck-Längsrandes (3) des Nachbar-Paneels. Ferner ist in Gebrauchsstellung zwischen der Stirnseite (12) des Einsteck-Längsrandes (3) und dem Nutengrund (13) des Aufnahme-Längsrandes (2) sowie sonstigen in Einsteckrichtung voreinander stehenden Vorsprüngen oder Flächen dieser beiden Ränder jeweils ein Spiel vorgesehen, so daß trotz der formschlüssigen Verbindung Wärmedehnungen weitgehend ohne Verformungen der eigentlichen Paneele möglich sind (Fig. 1).

IPC 1-7

E04F 13/12

IPC 8 full level

E04C 2/292 (2006.01); **E04F 13/12** (2006.01)

CPC (source: EP)

E04C 2/292 (2013.01); **E04F 13/12** (2013.01)

Citation (applicant)

- US 4104840 A 19780808 - HEINTZ DENNIS RONALD, et al
- DE 2917025 A1 19801127 - REYNOLDS ALUMINIUM FRANCE S A
- DE 7102476 U

Cited by

US8038363B2; US7896571B1; FR2832470A1; DE102006028496B3; DE102005039508A1; DE102005039508B4; US11578495B2; US10138637B2; US10876301B2; US8276342B2; WO03044303A1; US9605436B2; US9970199B2; US10801213B2; US10941578B2; WO0063510A1; US9624676B2; US9856657B2; US10125498B2; US10407920B2; US10508457B2; EP3087230B1; US9611656B2; US9677285B2; US10156078B2; US10233653B2; US10626619B2

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0220389 A2 19870506; **EP 0220389 A3 19871202**; **EP 0220389 B1 19900502**; AT E53884 T1 19900615; DE 3538538 A1 19870507; DE 3538538 C2 19901122; DE 3670874 D1 19900607

DOCDB simple family (application)

EP 86110166 A 19860724; AT 86110166 T 19860724; DE 3538538 A 19851030; DE 3670874 T 19860724