

Title (en)

METHOD FOR THE SEPARATION OF WATER OBTAINED FORM A COKING PROCESS INTO A SMALL HIGH SALT CONTENT FRACTION AND A LARGE LOW SALT CONTENT FRACTION

Publication

**EP 0221061 B1 19881012 (DE)**

Application

**EP 85902990 A 19850619**

Priority

DE 3423798 A 19840628

Abstract (en)

[origin: WO8600332A1] In order to separate water obtained in a coking process into a small fraction with a high salt content and into a large fraction with a low salt content, raw gas is cooled in a receiver and is conducted through an electric filter before entering the pre-cooler. The condensate of the receiver and the flow of the electrofilter are conducted into the tar separator, while the condensate of the pre-cooler is only partly reintroduced in the receiver circuit and a low salt content residue is obtained. On the other hand, the aqueous phase of the tar separator is partly treated as a high salt content fraction; after coming out of the electric filter, the raw gas may also be fractionated in a plurality of pre-coolers.

IPC 1-7

**C10K 1/00**

IPC 8 full level

**C10K 1/00** (2006.01); **B01D 50/00** (2006.01); **B01D 51/00** (2006.01); **B01D 51/10** (2006.01); **C10K 1/02** (2006.01); **C10K 1/04** (2006.01); **C10K 1/06** (2006.01)

CPC (source: EP KR US)

**C10K 1/00** (2013.01 - EP KR US); **C10K 1/001** (2013.01 - EP US); **C10K 1/06** (2013.01 - EP US)

Cited by

WO0160953A1

Designated contracting state (EPC)

BE DE FR GB IT NL SE

DOCDB simple family (publication)

**WO 8600332 A1 19860116**; DE 3423798 A1 19860109; DE 3423798 C2 19881201; DE 3565554 D1 19881117; EP 0221061 A1 19870513; EP 0221061 B1 19881012; JP H041793 B2 19920114; JP S61502540 A 19861106; KR 860700134 A 19860331; KR 900005099 B1 19900719; US 4710302 A 19871201

DOCDB simple family (application)

**EP 8500298 W 19850619**; DE 3423798 A 19840628; DE 3565554 T 19850619; EP 85902990 A 19850619; JP 50277785 A 19850619; KR 860700049 A 19860128; US 83338886 A 19860214