

Title (en)

Device for the motorized opening and closing of a door.

Title (de)

Motorisierte Vorrichtung zur Erzeugung der Öffnungs- und Schliessbewegungen eines Tores.

Title (fr)

Dispositif de commande motorisée pour l'ouverture et la fermeture d'un portail.

Publication

EP 0221827 A1 19870513 (FR)

Application

EP 86420259 A 19861021

Priority

- FR 8516320 A 19851025
- FR 8614346 A 19861009

Abstract (en)

1. A device for the motorized opening and closing of a door, intended more particularly for a door having two pivoting leaves (1, 2) and including, to operate each leaf, a "tubular" electric motor (15) mounted along the vertical pivotal axis (16) of the leaf (1, 2) and housed in the upper portion of a hollow lateral vertical element (6) of the leaf, the stator of the motor (15) being rigid with the upper pivot (3) of the leaf (1, 2), whilst its rotor is rotatably connected to the element (6) of the leaf by means of a speed reduction gear and drive shaft (19), characterized in that the drive shaft (19) of the or each leaf (1, 2), the axis of which shaft coincides with the vertical pivotal axis (16) of the leaf, is coupled to the element (6) of the leaf by way of "cam" type means (23) which, on the one hand, ensures a rotary connection between the drive shaft (19) and the leaf (1, 2), when the latter is free to pivot about the aforementioned axis (16), and which, on the other hand, is adapted to transform the rotational movement of the drive shaft (19) into a vertical translational movement of the relevant element (6) of the leaf (1, 2), when the latter is prevented from pivoting.

Abstract (fr)

Le dispositif comporte, pour actionner chaque vantail (1), un moto-réducteur électrique (15) monté suivant l'axe de pivotement (16) du vantail, à l'intérieur d'un montant latéral (6) de ce vantail. L'arbre de sortie (19) du moto-réducteur (15) porte des galets (21), qui coopèrent avec des doubles rampes inclinées (25) appartenant à une pièce (23) solidaire du montant (6). La liaison ainsi réalisée permet l' entraînement en rotation du vantail (1) lorsqu'il celui-ci est libre de pivoter, et elle provoque un déplacement vertical limité du vantail quand ce dernier est empêché de pivoter par la présence d'un obstacle, tel qu'une butée, sur son passage.

IPC 1-7

E05F 15/12

IPC 8 full level

E05F 15/00 (2006.01); **E05F 15/12** (2006.01); **E06B 11/02** (2006.01)

CPC (source: EP)

E05F 15/41 (2015.01); **E05F 15/614** (2015.01); **E05Y 2201/434** (2013.01); **E05Y 2800/28** (2013.01); **E05Y 2900/40** (2013.01)

Citation (search report)

- [AD] EP 0015857 A1 19800917 - LAUZIER RENE
- [A] DE 3121136 A1 19821216 - MAGNETIC ELEKTROMOTOREN GMBH [DE]
- [A] DE 3219192 A1 19831124 - UNTERREITER ERICH
- [A] JP S5612482 A 19810206 - AISIN SEIKI, et al
- [A] US 1386621 A 19210809 - SHERIDAN HUGHES ARTHUR

Cited by

CN105041181A; CN110043154A; FR2707695A1; FR2644507A1; CN114352081A; FR2800122A1

Designated contracting state (EPC)

AT BE CH DE ES GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0221827 A1 19870513; EP 0221827 B1 19890524; DE 3663553 D1 19890629; ES 2008858 B3 19890816; GR 3000121 T3 19901129;
JP H068585 B2 19940202; JP S62111087 A 19870522

DOCDB simple family (application)

EP 86420259 A 19861021; DE 3663553 T 19861021; ES 86420259 T 19861021; GR 890400138 T 19890804; JP 25213286 A 19861024