

Title (en)

LID MADE OF LAMINATE WITH AN OPENING CLOSED BY A STRIP MEMBER,AND METHOD FOR MAKING IT

Publication

EP 0221843 B1 19890614 (DE)

Application

EP 86810402 A 19860904

Priority

CH 429485 A 19851004

Abstract (en)

[origin: EP0221843A1] 1. A lid of a laminate material with an opening sealed with a tear-off strip, characterized in that a plastics insert (13) having a rim (17) is inserted into the stamped out opening (3) in the lid (1) and the rim (17) of the plastics insert (13) which extends into the region adjacent to the opening (3) and overlaps the opening (3) is bonded or sealed to the lid (1) and that an intended point of fracture is located between the rim (17) and the central portion of the plastics insert (13) forming the seal (15) in the form of a thin connection (21) and in that the tear-off strip covering the opening (3) from above is sealed to the seal (15) and the region of the lid (1) surrounding the seal (15), wherein the connection with the seal (15) cannot be released and the connection with the lid (1) can be peeled apart.

IPC 1-7

B65D 17/50

IPC 8 full level

B65D 17/50 (2006.01)

CPC (source: EP US)

B65D 17/502 (2013.01 - EP); **B65D 17/505** (2013.01 - EP); **B65D 17/506** (2013.01 - EP US); **B65D 2517/0013** (2013.01 - EP); **B65D 2517/0086** (2013.01 - EP); **B65D 2517/5027** (2013.01 - EP); **B65D 2517/5064** (2013.01 - EP); **B65D 2517/5083** (2013.01 - EP)

Citation (examination)

GB 1389351 A 19750403 - NAT CAN CORP

Cited by

WO2014127887A1; WO2016119799A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0221843 A1 19870513; **EP 0221843 B1 19890614**; AT E44008 T1 19890615; DE 3663925 D1 19890720

DOCDB simple family (application)

EP 86810402 A 19860904; AT 86810402 T 19860904; DE 3663925 T 19860904