

Title (en)

CONTINUOUS PICKLING METHOD AND APPARATUS

Publication

EP 0225273 B1 19900328 (EN)

Application

EP 86730180 A 19861103

Priority

- JP 27343185 A 19851206
- JP 27506785 A 19851209
- JP 27506885 A 19851209

Abstract (en)

[origin: EP0225273A1] The present invention is directed to a continuous pickling method for continuously pickling a material to be pickled, the method being characterised by heating the material up to a temperature higher than a boiling point of an acid liquid under atmospheric pressure, and then pickle the material; a continuous pickling method characterized in that in the pickling process, the acid liquid is jetted against the material, without immersing the material into the acid liquid; and a continuous pickling pretreating apparatus, used in the above mentioned continuous pickling methods, which comprises a tank for receiving herein hot water having a temperature higher than its boiling point under atmospheric pressure, a heating device for heating the hot water, and seal rolls disposed at an outlet and an inlet of the tank and the material.

IPC 1-7

C23G 1/02; **C23G 3/02**

IPC 8 full level

C23G 1/02 (2006.01); **C23G 3/02** (2006.01)

CPC (source: EP KR)

C23G 1/00 (2013.01 - KR); **C23G 1/02** (2013.01 - EP); **C23G 3/023** (2013.01 - EP); **C23G 3/028** (2013.01 - EP)

Cited by

US5466309A; CN102644087A; FR2701493A1; CN105483741A; AT500729B1; FR2701410A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0225273 A1 19870610; **EP 0225273 B1 19900328**; AU 594988 B2 19900322; AU 6550186 A 19870611; BR 8605681 A 19870818; DE 3669898 D1 19900503; KR 870006236 A 19870710

DOCDB simple family (application)

EP 86730180 A 19861103; AU 6550186 A 19861118; BR 8605681 A 19861117; DE 3669898 T 19861103; KR 860010118 A 19861128