

Title (en)
LOOM AND PROCESS FOR APPLYING A CONTROL UNIT TO THE LOOM

Publication
EP 0225517 B1 19900131 (DE)

Application
EP 86116050 A 19861120

Priority
CH 515785 A 19851204

Abstract (en)
[origin: US4706714A] The cross beam of the loom is provided with a retaining bar in which at least one panel-like or board-like switching unit is slidably mounted. Suitable access openings are provided in the retaining bar to permit access to the control elements on the switching unit. Panel like spacing elements are employed to locate the respective switching units within the retaining bar and electrical plugs are provided for connecting the switching units to a flat cable extending along the cross beam.

IPC 1-7
D03D 49/02

IPC 8 full level
D03D 49/00 (2006.01); **D03D 49/02** (2006.01); **D03D 51/00** (2006.01); **D03D 51/02** (2006.01)

CPC (source: EP US)
D03D 49/02 (2013.01 - EP US)

Cited by
CN107313162A; US6213160B1

Designated contracting state (EPC)
BE DE FR IT

DOCDB simple family (publication)
EP 0225517 A1 19870616; EP 0225517 B1 19900131; BR 8605952 A 19870915; CH 669223 A5 19890228; DE 3668648 D1 19900308; JP H0788612 B2 19950927; JP S62133152 A 19870616; US 4706714 A 19871117

DOCDB simple family (application)
EP 86116050 A 19861120; BR 8605952 A 19861204; CH 515785 A 19851204; DE 3668648 T 19861120; JP 28864986 A 19861203; US 93721386 A 19861203