

Title (en)

Brick for a bottom electrode, a rear lining or a hearth connection.

Title (de)

Ziegel für Bodenelektrode, Ofenauskleidung oder Verbindung zu einem Tiegel.

Title (fr)

Brique pour électrode de fond, pour revêtement d'un four, ou connexion à un creuset.

Publication

EP 0225548 A2 19870616 (EN)

Application

EP 86116468 A 19861127

Priority

SE 8505660 A 19851202

Abstract (en)

Brick for a bottom electrode, a rear lining or a hearth connection for a.d.c. arc furnace. According to the invention the brick consist of a porous material which has been impregnated by means of immersion into and/or spraying with an organic fluid, such as pitch, tar or a suspension of graphite, soot or the like, or synthetic resin, whereafter the brick has been coked, for example at a temperature of 350 DEG C, thus creating electric current carrying paths containing coal which paths render the brick electrically conductive.

IPC 1-7

H05B 7/06; **F27D 1/06**

IPC 8 full level

C04B 41/85 (2006.01); **F27B 3/10** (2006.01); **F27D 1/00** (2006.01); **F27D 1/06** (2006.01); **H01B 1/18** (2006.01); **H05B 7/06** (2006.01)

CPC (source: EP)

F27D 1/0006 (2013.01); **F27D 1/063** (2013.01); **H05B 7/06** (2013.01)

Cited by

CN107244930A

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0225548 A2 19870616; **EP 0225548 A3 19880608**; **EP 0225548 B1 19930804**; DE 3688830 D1 19930909; DE 3688830 T2 19940303; JP 2605024 B2 19970430; JP S62143888 A 19870627; SE 456878 B 19881107; SE 8505660 D0 19851202; SE 8505660 L 19870603; ZA 869000 B 19870624

DOCDB simple family (application)

EP 86116468 A 19861127; DE 3688830 T 19861127; JP 28410686 A 19861128; SE 8505660 A 19851202; ZA 869000 A 19861128