

Title (en)

METHOD OF MANUFACTURING AN ELECTROMAGNETIC RELAY WITHOUT ADJUSTING

Publication

**EP 0226891 B1 19900926 (DE)**

Application

**EP 86116738 A 19861202**

Priority

DE 3543099 A 19851205

Abstract (en)

[origin: US4742610A] An electromagnetic relay having a contact tongue arranged extending within a base body and switchable between two pole plates, the contact tongue having an end secured by a hard fastening adhesive, the adjustment of the contact tongue between the pole plates occurs by periodically switching an alternating excitation current during solidification of the adhesive.

IPC 1-7

**H01H 49/00**

IPC 8 full level

**H01H 49/00** (2006.01)

CPC (source: EP US)

**H01H 49/00** (2013.01 - EP US); **Y10T 29/4902** (2015.01 - EP US); **Y10T 29/49105** (2015.01 - EP US)

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0226891 A1 19870701**; **EP 0226891 B1 19900926**; AT E57043 T1 19901015; DE 3674554 D1 19901031; ES 2017621 B3 19910301; JP H0711934 B2 19950208; JP S62139226 A 19870622; US 4742610 A 19880510

DOCDB simple family (application)

**EP 86116738 A 19861202**; AT 86116738 T 19861202; DE 3674554 T 19861202; ES 86116738 T 19861202; JP 28912086 A 19861205; US 93852886 A 19861205