

Title (en)
Fire detector.

Title (de)
Feuerdetektor.

Title (fr)
Détecteur de fumée.

Publication
EP 0227320 A2 19870701 (EN)

Application
EP 86309241 A 19861126

Priority
GB 8529435 A 19851129

Abstract (en)
A fire detector to be disposed on a mounting surface such as a ceiling, comprising a chamber open to the ambient atmosphere the chamber having a base, a peripheral region of which lies in a single plane preferably parallel with the surface when the detector is mounted thereon, the base being formed inwardly of the peripheral region with a pair of oppositely sloped recesses meeting at a generally central ridge extending across the base laterally of the recesses, an optical source mounted at the end remote from the ridge of one of the recesses with its optimum optical path directed therealong and an optical receiver mounted at the end remote from the ridge of the other recess with its optimum optical path facing therealong, characterised in that said optimum optical paths are each at a different angle to said plane so that the optical axes of the source and the receiver meet at an angle between 170 DEG and 135 DEG at a position within the chamber spaced laterally from the ridge.

IPC 1-7
G08B 17/10

IPC 8 full level
G08B 17/107 (2006.01)

CPC (source: EP)
G08B 17/107 (2013.01); **G08B 17/113** (2013.01)

Cited by
FR2928220A1; EP1327966A3; CN113168753A; AT17840U1; US5898377A; EP0800153A3; GB2308978A; GB2308978B; US11869327B2; US6914535B2; WO9704429A1; WO9709876A1; WO2009115720A3

Designated contracting state (EPC)
CH DE GB LI

DOCDB simple family (publication)
EP 0227320 A2 19870701; **EP 0227320 A3 19880803**; **EP 0227320 B1 19950104**; DE 3650197 D1 19950216; DE 3650197 T2 19950511; GB 8529435 D0 19860108

DOCDB simple family (application)
EP 86309241 A 19861126; DE 3650197 T 19861126; GB 8529435 A 19851129