

Title (en)

SAFETY LOCK, OBJECT, ESPECIALLY A PIECE OF LUGGAGE, AND AN INSTALLATION FOR APPLYING IT

Publication

EP 0227507 B1 19890426 (FR)

Application

EP 86402454 A 19861103

Priority

FR 8516858 A 19851114

Abstract (en)

[origin: US4813253A] A closing device includes a keeper provided with a retaining element for retaining a bolt in the keeper in a closed position of the device. The retaining element is mounted to be pivotable about and to be axially movable on a rod provided in the keeper and is resiliently biased to both axially slide on and pivot about the rod in such manner that, in an active position, the retaining element projects into an extension of an opening into which the bolt is capable of entering so as to close the device, and it is brought to a retracted position by axially sliding along the rod while being automatically returned to its active position from its retracted position as soon as the bolt is extracted from the keeper under the effect of the resilient force exerted by a spring.

IPC 1-7

E05C 5/00

IPC 8 full level

A45C 13/10 (2006.01); **E05C 5/00** (2006.01)

CPC (source: EP US)

E05C 5/00 (2013.01 - EP US); **Y10T 70/5058** (2015.04 - EP US); **Y10T 70/5062** (2015.04 - EP US); **Y10T 70/5071** (2015.04 - EP US); **Y10T 70/508** (2015.04 - EP US); **Y10T 70/5089** (2015.04 - EP US); **Y10T 70/5124** (2015.04 - EP US); **Y10T 70/5354** (2015.04 - EP US)

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

US 4813253 A 19890321; AT E42596 T1 19890515; CA 1274401 A 19900925; DE 3663052 D1 19890601; DK 165646 B 19921228; DK 165646 C 19930517; DK 544086 A 19870515; DK 544086 D0 19861113; EP 0227507 A1 19870701; EP 0227507 B1 19890426; ES 2009126 B3 19890901; FR 2589931 A1 19870515; FR 2589931 B1 19900601; GR 3000053 T3 19901031; HK 96990 A 19901130; JP S63302804 A 19881209; SG 29990 G 19901026

DOCDB simple family (application)

US 93158186 A 19861114; AT 86402454 T 19861103; CA 522821 A 19861113; DE 3663052 T 19861103; DK 544086 A 19861113; EP 86402454 A 19861103; ES 86402454 T 19861103; FR 8516858 A 19851114; GR 890400052 T 19890427; HK 96990 A 19901122; JP 27273586 A 19861114; SG 29990 A 19900419