

Title (en)
SPACER FOR ARMOURINGS IN A FORMWORK

Publication
EP 0227762 B1 19900411 (DE)

Application
EP 86904127 A 19860609

Priority
DE 3521345 A 19850614

Abstract (en)
[origin: DE3521345A1] Spacer (31), particularly in a concrete wall, comprised of a spacer bar (1), of at least a flat part (1) which, at the higher region (2) is firmly connected to the spacing bar (11), and of a spring element (20), an armouring bar (35) being set in place between the flat part (1) and the spring element (20). The flat part (1) is provided with a lateral recess (13) intended to house at least partially the armouring bar (35). A section (24) of the spring element (20) is directly arranged before the side (12) provided with a recess (13) of the flat part (1) and in the main plane of the latter, the configuration of the spring element (20) acting as grippers, enabling it to be elastically spaced apart laterally with respect to the side (12) of the flat part (1).

IPC 1-7
E04C 5/16

IPC 8 full level
E04C 5/16 (2006.01)

CPC (source: EP)
E04C 5/168 (2013.01)

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
DE 3521345 A1 19861218; DE 3521345 C2 19900628; AU 6142486 A 19870107; DE 3670333 D1 19900517; EP 0227762 A1 19870708; EP 0227762 B1 19900411; ES 295468 U 19870101; ES 295468 Y 19870916; PT 82750 A 19860701; PT 82750 B 19920831; WO 8607401 A1 19861218; ZA 864429 B 19870225

DOCDB simple family (application)
DE 3521345 A 19850614; AU 6142486 A 19860609; DE 3670333 T 19860609; EP 8600344 W 19860609; EP 86904127 A 19860609; ES 295468 U 19860613; PT 8275086 A 19860612; ZA 864429 A 19860613