

Title (en)
STOP

Publication
EP 0229760 B1 19890705 (EN)

Application
EP 85905245 A 19851017

Priority
SE 8405335 A 19841025

Abstract (en)
[origin: WO8602691A1] Stop for retaining, when so desired, a door leaf (2) suspended from a frame (1) by means of a number of hinges (3), in an open position. The stop has two abutment bodies (6, 6') which are interconnected by means of a thin central piece (7). The central piece and at least one abutment body have a smaller thickness than the gap formed between the door leaf and the frame when the door is open, such that this abutment body and the central piece can be inserted through the gap. By turning the stop 90° after insertion thereof, it is activated, such that the door leaf is locked in the open position.

IPC 1-7
E05C 17/54; E05F 5/06

IPC 8 full level
E05C 17/02 (2006.01)

CPC (source: EP)
E05C 17/025 (2013.01)

Citation (examination)
SE 8204452 A

Cited by
EP3430611A4; USD893587S; WO2017160888A1; USD888147S; USD888146S

Designated contracting state (EPC)
DE FR GB IT NL

DOCDB simple family (publication)
WO 8602691 A1 19860509; DE 3571335 D1 19890810; DK 156140 B 19890626; DK 156140 C 19891113; DK 297586 A 19860624;
DK 297586 D0 19860624; EP 0229760 A1 19870729; EP 0229760 B1 19890705; SE 444204 B 19860324; SE 8405335 D0 19841025;
SE 8405335 L 19860324

DOCDB simple family (application)
SE 8500400 W 19851017; DE 3571335 T 19851017; DK 297586 A 19860624; EP 85905245 A 19851017; SE 8405335 A 19841025