

Title (en)
VALVE ARRANGEMENT FOR HYDRAULIC ACCUMULATOR

Publication
EP 0230529 A3 19890426 (DE)

Application
EP 86114822 A 19861024

Priority
DE 3602362 A 19860127

Abstract (en)
[origin: US4706930A] A valve arrangement for connecting a hydraulic machine, such as a pump or a motor, with a pressure accumulator in which a conventional manual shutoff valve is replaced by a leak-proof pressure controlled valve whose operating pressure signal is supplied by a shuttle valve from that one of two ports of the pressure controlled valve at which the higher pressure prevails at a given time. The pressure controlled valve is supplied with fluid under pressure by way of a leak-proof remote controlled slide valve.

IPC 1-7
F15B 1/02

IPC 8 full level
F15B 1/02 (2006.01); **F15B 13/042** (2006.01)

CPC (source: EP US)
F15B 1/02 (2013.01 - EP US); **F15B 2013/0428** (2013.01 - EP US); **Y10T 137/87209** (2015.04 - EP US)

Citation (search report)

- [Y] DE 3113933 A1 19821028 - BOSCH GMBH ROBERT [DE]
- [Y] US 4149565 A 19790417 - JENNINGS MARVIN D, et al
- [A] US 2683966 A 19540720 - RANSOM TYLER
- [A] US 3533434 A 19701013 - SMITH ROBERT JAMES
- [A] FR 2381192 A1 19780915 - FRANK ROGER [FR]
- [A] US 4340086 A 19820720 - HEMM ANSGAR, et al

Cited by
US5477677A; DE4438899C1; EP2603705A4; DE19638837A1; DE19638837B4; DE4223389A1; US5558004A; DE4223389C2

Designated contracting state (EPC)
AT CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0230529 A2 19870805; EP 0230529 A3 19890426; EP 0230529 B1 19920219; AT E72693 T1 19920315; DE 3602362 A1 19870730; DE 3683933 D1 19920326; DK 166551 B1 19930607; DK 578386 A 19870728; DK 578386 D0 19861202; US 4706930 A 19871117

DOCDB simple family (application)
EP 86114822 A 19861024; AT 86114822 T 19861024; DE 3602362 A 19860127; DE 3683933 T 19861024; DK 578386 A 19861202; US 92274786 A 19861024