

Title (en)

GRINDER FOR CORE OF OPTICAL CONNECTOR AND CORE GRINDING METHOD

Publication

EP 0231397 B1 19920304 (EN)

Application

EP 86904925 A 19860807

Priority

JP 17347685 A 19850807

Abstract (en)

[origin: EP0231397A1] Technique for grinding an end surface of a core (2) of an optical connector used for connecting an optical fiber (11), to grind the same into a convex surface. A grinder (3) is provided with at least a layer (4) of a low-elasticity material, and a grinding layer (6) laminated unitarily on the upper surface of the layer (4). The JIS-A hardness and Shore hardness of the layer (4) of the low-elasticity material are set to be not less than 50 DEG and not more than 60 DEG , respectively. When the surface of such a grinder and the end surface of the core (2) of an optical connector are brought into contact with each other with a suitable pressing force, the surface of the grinder (3) is recessed to form a concave surface. Accordingly, the end surface of the core (2) of the connector can be ground into a convex surface by utilizing this recession.

IPC 1-7

B24B 11/00; B24B 11/06; G02B 6/00; G02B 6/32

IPC 8 full level

G02B 6/00 (2006.01); **B24B 7/16** (2006.01); **B24B 11/00** (2006.01); **B24B 11/06** (2006.01); **B24B 19/00** (2006.01); **B24B 19/22** (2006.01);
B24D 9/08 (2006.01); **G02B 6/32** (2006.01)

CPC (source: EP KR)

B24B 7/16 (2013.01 - EP); **B24B 11/00** (2013.01 - EP KR); **B24B 19/226** (2013.01 - EP)

Citation (examination)

EP 0147633 A2 19850710 - ELBEL RABERAIN ANNE MARIE

Cited by

US10543582B2; WO2020046781A1; US10866368B2

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0231397 A1 19870812; EP 0231397 A4 19890313; EP 0231397 B1 19920304; AU 6200086 A 19870305; CA 1322457 C 19930928;
DE 3684135 D1 19920409; JP S6234762 A 19870214; KR 870700454 A 19871229; KR 930007108 B1 19930730; NZ 217135 A 19890106;
WO 8700785 A1 19870212

DOCDB simple family (application)

EP 86904925 A 19860807; AU 6200086 A 19860807; CA 515499 A 19860807; DE 3684135 T 19860807; JP 17347685 A 19850807;
JP 8600406 W 19860807; KR 870700291 A 19870403; NZ 21713586 A 19860807