

Title (en)
METHOD AND DEVICE FOR ELECTRONICALLY CONTROLLING FUEL INJECTION DEVICE

Publication
EP 0231887 B1 19900411 (EN)

Application
EP 87101238 A 19870129

Priority
JP 1795286 A 19860131

Abstract (en)
[origin: EP0231887A2] A fuel at the time of start of an internal combustion engine (8) is supplied dividedly by the injection pulse signals. The injection pulse width (T_{ST}) of the injection pulse signals is controlled in accordance with the temperature of the engine fuel chamber (9) of the internal combustion engine.

IPC 1-7
F02D 41/06; **F02D 41/34**

IPC 8 full level
F02D 41/00 (2006.01); **F02D 41/06** (2006.01); **F02D 41/34** (2006.01)

CPC (source: EP KR US)
F02D 41/062 (2013.01 - EP US); **F02D 41/064** (2013.01 - EP US); **F02D 41/34** (2013.01 - KR); **F02D 2200/503** (2013.01 - EP US)

Cited by
DE102012000688B4; GB2285144A; DE4446081A1; GB2285144B

Designated contracting state (EPC)
DE GB

DOCDB simple family (publication)
EP 0231887 A2 19870812; **EP 0231887 A3 19870909**; **EP 0231887 B1 19900411**; DE 3762261 D1 19900517; JP H06103005 B2 19941214; JP S62178739 A 19870805; KR 870007353 A 19870818; KR 900003854 B1 19900602; US 4719885 A 19880119

DOCDB simple family (application)
EP 87101238 A 19870129; DE 3762261 T 19870129; JP 1795286 A 19860131; KR 870000657 A 19870128; US 992187 A 19870202