

Title (en)

Crate made from a foldable blank.

Title (de)

Steige aus einem faltbaren Zuschnitt.

Title (fr)

Cageot formé à partir d'un flan repliable.

Publication

**EP 0234234 A2 19870902 (DE)**

Application

**EP 87100534 A 19870116**

Priority

DE 8601439 U 19860122

Abstract (en)

The crate is made of an integral foldable blank which consists of a bottom, to which in each case opposite end and side walls are attached, of which the side walls each bear at their upper longitudinal edge a perforated plate provided with recesses for the positionally secure accommodation of containers or the like. The perforated plate has a width corresponding to approximately half the width of the bottom and lid support tabs which are folded downwards, are punched from one of said recesses in each case and are bonded to attachment strips which are punched out of the bottom, are bent upwards in opposite directions and lie parallel to the side walls. In order to improve the rigidity, it is proposed that in each case two attachment strips, together with the lid support tabs bonded to their inside, form a hollow support web, which tapers conically upwards in cross-section, between the perforated plate and the bottom.

Abstract (de)

Die Erfindung betrifft eine Steige aus einem einstückigen faltbaren Zuschnitt, bestehend aus einem Boden, an den sich jeweils gegenüberliegende Stirn- und Seitenwandungen (2, 3) angelenkt sind, von denen die Seitenwandungen (3) an ihrem oberen Längsrand (4) je eine mit Ausnehmungen (6) zur lagesicheren Aufnahme von Behältern o. dgl. versehene Lochplatte (5) tragen, die eine etwa der halben Bodenbreite entsprechende Breite und nach unten umgefaltete Deckelstützlaschen (7) aufweist, die jeweil aus einer der genannten Ausnehmungen ausgestanzt und mit aus dem Boden ausgestanzten, in entgegengesetzte Richtungen nach oben umgebogenen, parallel zu den Seitenwandungen liegenden Befestigungsstreifen verklebt sind. Zur Verbesserung der Steifigkeit wird vorgeschlagen, daß je zwei Befestigungsstreifen zusammen mit den gegen ihre Innenseite geklebten Deckelstützlaschen einen hohlen, sich im Querschnitt nach oben konisch verjüngenden Stützsteg zwischen Lochplatte und Boden bilden.

IPC 1-7

**B65D 71/00**

IPC 8 full level

**B65D 71/72** (2006.01)

CPC (source: EP)

**B65D 71/72** (2013.01)

Cited by

FR2695103A1; EP0694382A1; FR2723029A1; GB2240323A; GB2240323B

Designated contracting state (EPC)

CH DE ES FR GB IT LI NL

DOCDB simple family (publication)

**DE 8601439 U1 19860227**; EP 0234234 A2 19870902; EP 0234234 A3 19880928; PT 84163 A 19870201; PT 84163 B 19910320

DOCDB simple family (application)

**DE 8601439 U 19860122**; EP 87100534 A 19870116; PT 8416387 A 19870121