

Title (en)

PROCESS FOR ADJUSTING THE WIDTH OF THE GAP IN A CONE-TYPE CRUSHER OR SIMILAR

Publication

EP 0236392 B1 19890614 (DE)

Application

EP 86905285 A 19860909

Priority

AT 263485 A 19850910

Abstract (en)

[origin: WO8701305A1] To adjust the width of the gap in cone-type crushers the reference position is first determined by bringing the crushing cone close to the fixed casing of the crusher. Using this reference position, it is then possible to move the crusher cone to its operating position, which corresponds to the predetermined gap width. To improve the accuracy of the adjustment process taking into account uneven wear in the region of the crusher cone and crusher casing, the solution proposed is to perform several successive approach cycles of the rotating crusher cone, to record the approach values thus obtained and finally to establish a reference value which determines the reference position.

IPC 1-7

B02C 2/06; **B02C 25/00**

IPC 8 full level

B02C 2/04 (2006.01); **B02C 2/06** (2006.01); **B02C 25/00** (2006.01)

CPC (source: EP US)

B02C 2/047 (2013.01 - EP US); **B02C 2/06** (2013.01 - EP US); **B02C 25/00** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

WO 8701305 A1 19870312; AT 389653 B 19900110; AT A263485 A 19890615; AT E43975 T1 19890615; AU 594369 B2 19900308; AU 6288586 A 19870324; DE 3663888 D1 19890720; EP 0236392 A1 19870916; EP 0236392 B1 19890614; JP S63500708 A 19880317; US 4793560 A 19881227

DOCDB simple family (application)

EP 8600519 W 19860909; AT 263485 A 19850910; AT 86905285 T 19860909; AU 6288586 A 19860909; DE 3663888 T 19860909; EP 86905285 A 19860909; JP 50477586 A 19860909; US 6143487 A 19870511