

Title (en)

CONNECTION BETWEEN THE CASING AND THE BOTTOM OF A SABOT FOR A SUBCALIBRE PROJECTILE

Publication

**EP 0236705 B1 19891129 (DE)**

Application

**EP 87100901 A 19870123**

Priority

CH 95186 A 19860307

Abstract (en)

[origin: US4726298A] Ever greater demands in terms of mechanical strength and gas tightness are being made on the connection between the rear part and the casing of a sabot for a projectile. To improve this connection a circumferential groove is provided in the rear part of the sabot into which protrudes a rotating band of the sabot casing which band contacts the barrel rifling to spin or rotate the projectile. The circumferential groove and the rotating band anchored therein exhibit a dovetailed cross-section which prevents the rotating band from slipping out of the circumferential groove. The rotating band is linked to the casing via a predetermined break point.

IPC 1-7

**F42B 13/16**

IPC 8 full level

**F42B 14/06** (2006.01)

CPC (source: EP US)

**F42B 14/064** (2013.01 - EP US)

Designated contracting state (EPC)

BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0236705 A1 19870916; EP 0236705 B1 19891129;** CA 1274416 A 19900925; DE 3761061 D1 19900104; IL 81635 A0 19870916; IL 81635 A 19911121; JP S62210398 A 19870916; NO 162045 B 19890717; NO 162045 C 19891025; NO 870924 D0 19870305; NO 870924 L 19870908; US 4726298 A 19880223; ZA 871638 B 19870826

DOCDB simple family (application)

**EP 87100901 A 19870123;** CA 530032 A 19870218; DE 3761061 T 19870123; IL 8163587 A 19870220; JP 4898887 A 19870305; NO 870924 A 19870305; US 1784387 A 19870224; ZA 871638 A 19870306