

Title (en)
PROCESS FOR MANUFACTURING CONTACT MEMBERS

Publication
EP 0236963 B1 19921223 (DE)

Application
EP 87103171 A 19870306

Priority
DE 3608276 A 19860312

Abstract (en)
[origin: US4752253A] A contact element in the form of a spring contact jack or spring plug pin has a plurality of mutually laterally disposed spring contacts which can be attached at one end to a support piece and which are radially curved in order to provide contact with an opposing contact; and further relates to a method of manufacturing the contact element.

IPC 1-7
H01R 13/05; H01R 13/11; H01R 13/33

IPC 8 full level
H01R 13/05 (2006.01); **H01R 13/11** (2006.01); **H01R 13/187** (2006.01); **H01R 13/33** (2006.01); **H01R 43/16** (2006.01)

CPC (source: EP US)
H01R 13/05 (2013.01 - EP US); **H01R 13/11** (2013.01 - EP US); **H01R 13/17** (2013.01 - EP US); **H01R 43/16** (2013.01 - EP US)

Cited by
EP2320525A4; EP3544123A4

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0236963 A2 19870916; EP 0236963 A3 19890118; EP 0236963 B1 19921223; AT E83875 T1 19930115; DE 3608276 A1 19870917; DE 3783148 D1 19930204; ES 2000250 A4 19880201; ES 2000250 T3 19930601; GR 3007150 T3 19930730; JP H05198345 A 19930806; JP H06101361 B2 19941212; JP S62223994 A 19871001; US 4752253 A 19880621

DOCDB simple family (application)
EP 87103171 A 19870306; AT 87103171 T 19870306; DE 3608276 A 19860312; DE 3783148 T 19870306; ES 87103171 T 19870306; GR 930400386 T 19930225; JP 25496992 A 19920924; JP 5548087 A 19870312; US 2520987 A 19870312