

Title (en)
CLADDING ASSEMBLY AND METHOD

Publication
EP 0237333 A3 19880210 (EN)

Application
EP 87302075 A 19870311

Priority
• GB 8605967 A 19860311
• GB 8701529 A 19870123

Abstract (en)
[origin: EP0237333A2] To avoid the need for nailing through tiles and other cladding elements (10), they are formed with oppositely directed hook formations (30,32) at opposite edges. These engage support means, which may be retaining profiles (40) mounted on battens (50). For example, an upwardly facing hook formation (30) is engageable under a downwardly directed supporting tongue (46) when the element is tilted. It can then be pivoted about that tongue (76), into its cladding configuration. Its other hook formation (32) snap-engages behind the tongue (46) of the adjacent support means, which already engages the upwardly facing hook portion (30) of another cladding element. Each support profile (40) extends for most of the width of one or more elements (10) and provides support (48).

IPC 1-7
E04D 3/365; E04D 3/32; E04D 3/362

IPC 8 full level
E04D 3/32 (2006.01); **E04D 3/365** (2006.01)

CPC (source: EP)
E04D 3/32 (2013.01); **E04D 3/365** (2013.01)

Citation (search report)
• [A] DE 1055219 B 19590416 - ERIC SIGFRID PERSSON
• [A] DE 2539872 A1 19760318 - PETERSSON NEW PROD BENGT
• [A] US 4602469 A 19860729 - NUCKEL JR WILLIAM H [US]
• [A] AU 468407 A
• [A] US 3945166 A 19760323 - HOSODA KIYOSHI, et al

Cited by
EP0985780A1; GB2210393A; GB2210393B; WO9958784A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0237333 A2 19870916; EP 0237333 A3 19880210

DOCDB simple family (application)
EP 87302075 A 19870311