

Title (en)
METHOD AND DEVICE FOR OUTLINE SEWING

Publication
EP 0237803 B1 19920513 (DE)

Application
EP 87102136 A 19870216

Priority
CH 61986 A 19860217

Abstract (en)
[origin: US4841889A] The method of making contour seams on material to be sewn starts from a sewing position in which the material to be sewn has been clamped in spread manner, before the sewing operation, by means of three gripping points provided along a contour line. The contour line is defined by the pattern of the cut and superimposed fabric edges of pieces of material to be sewn together. The gripping point closest to the sewing-machine is stationary, and the two other gripping points are each supported so as to be movable in a polar coordinate system. Initiation of the sewing operation is effected each time with simultaneous release of the material to be sewn in the stationary gripping point, and in at least part of the sewing operation the stitch chain is guided parallel to the contour line in opto-electronic control.

IPC 1-7
D05B 35/10

IPC 8 full level
D05B 1/20 (2006.01); **D05B 35/10** (2006.01)

CPC (source: EP US)
D05B 35/102 (2013.01 - EP US); **D05D 2207/04** (2013.01 - EP US)

Designated contracting state (EPC)
AT CH DE FR GB IT LI

DOCDB simple family (publication)
EP 0237803 A2 19870923; EP 0237803 A3 19890315; EP 0237803 B1 19920513; AT E76126 T1 19920515; CH 670844 A5 19890714; DE 3778940 D1 19920617; JP S62266093 A 19871118; US 4841889 A 19890627

DOCDB simple family (application)
EP 87102136 A 19870216; AT 87102136 T 19870216; CH 61986 A 19860217; DE 3778940 T 19870216; JP 3436987 A 19870217; US 1444887 A 19870213