

Title (en)

DIFFERENTIAL GEAR FOR A BOLT LOCK, IN PARTICULAR FOR A MORTISE LOCK

Publication

**EP 0237832 A3 19880120 (DE)**

Application

**EP 87102522 A 19870223**

Priority

AT 72786 A 19860319

Abstract (en)

[origin: EP0237832A2] The lock has a pinion, which can be actuated by a lock bit, in the form of a slotted ring provided with pinion teeth and has a blocking pinion, there being arranged between the pinion and the blocking pinion further differential pinions, meshing with said pinions, and, if appropriate, gear pinions, connected to the differential pinions, for a permanent positive and/or non-positive coupling of these parts. The differential pinion (1) has recesses (2) which are provided, when the differential gear is actuated, in each case in their positions of rotation, facing the pinion (3), directly opposite the lock bit (5) arranged in the slot (4), by which means space is provided for the lock bit (5) to rotate past. <IMAGE>

IPC 1-7

**E05B 63/08**; **E05C 9/02**

IPC 8 full level

**E05B 17/04** (2006.01)

CPC (source: EP)

**E05B 17/042** (2013.01)

Citation (search report)

- [X] DE 3114777 A1 19821028 - BRUMME PRESS & STANZWERK [DE]
- [AD] FR 1190878 A 19591015 - RHETAISE IND ET COMMERCIALE SA
- [A] DE 2840285 A1 19790329 - LAPERCHÉ SA

Cited by

FR2707322A1; FR2690944A1; AT413124B; EP3048223A1; FR3031761A1; EP0770746A1; FR2740499A1; FR2708305A1; WO2009053973A3; WO2004040086A1

Designated contracting state (EPC)

CH DE FR GB IT LI NL

DOCDB simple family (publication)

**EP 0237832 A2 19870923**; **EP 0237832 A3 19880120**; AT 384266 B 19871027; AT A72786 A 19870315

DOCDB simple family (application)

**EP 87102522 A 19870223**; AT 72786 A 19860319