

Title (en)

METHOD FOR OPERATING AN EXTRUSION MILL AND EXTRUSION MILL FORUSE IN THIS METHOD

Publication

EP 0238147 B1 19900103 (EN)

Application

EP 87200497 A 19870318

Priority

NL 8600693 A 19860318

Abstract (en)

[origin: EP0238147A1] In an extrusion mill of the type of a pellet press, there are pressing rollers 7 rotating within a perforated drum 3 for pressing material through the openings in the drum e.g. for making pellets for feeding cattle. The invention relates to the adjustment of the rollers radially with respect to the drum during operation, by adjustment means extending to the outside opposite the side where the material to be pressed enters the drum. The rollers are first adjusted in positions close to the drum wall and are then gradually adjusted inwardly during pressing, to give better results, prevent clogging of the mill with tacky material therein and avoid the necessity to stop the mill and open it for each adjustment.

IPC 1-7

B30B 11/20

IPC 8 full level

B30B 11/20 (2006.01)

CPC (source: EP)

B30B 11/208 (2013.01)

Cited by

EP0694380A1; NL1004319C2; US5435713A; EP0371519A3; DE4426372A1; EP2105292A1; DE102008015617B4; WO2016195484A2; US6244850B1; WO9817464A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0238147 A1 19870923; EP 0238147 B1 19900103; EP 0238147 B2 19930512; AT E49155 T1 19900115; DE 3761295 D1 19900208; ES 2012384 B3 19900316; ES 2012384 T5 19950801; GR 3000270 T3 19910315

DOCDB simple family (application)

EP 87200497 A 19870318; AT 87200497 T 19870318; DE 3761295 T 19870318; ES 87200497 T 19870318; GR 890400300 T 19900104