

Title (en)  
ELECTRIC INSTALLATION EQUIPMENT

Publication  
**EP 0238960 B1 19920108 (DE)**

Application  
**EP 87103747 A 19870314**

Priority  
• DE 3610451 A 19860327  
• DE 3611754 A 19860408

Abstract (en)  
[origin: EP0238960A1] A low-voltage, high-rupture-capacity (hrc) fuse consists of a low-voltage, hrc fuse lower part (10) and a low-voltage, hrc fuse insert (22, 23), which is designed as an automatic circuit breaker. For this purpose, the commercial circuit breaker (23) is provided with connecting tabs (28) which lead to blade contacts (31) on the rear side of the circuit breaker (23). The blade contacts (31) are inserted in fork contacts (14, 15). A cover (60), which can be snapped onto the circuit breaker (23), is used for protection against touching. Furthermore, the cover (60) is provided with a coupling part (78), which is prepared for an extraction device for commercial low-voltage, hrc fuse inserts to be coupled on. <IMAGE>

IPC 1-7  
**H01H 71/08**

IPC 8 full level  
**H01H 71/08** (2006.01); **H01H 73/08** (2006.01); **H01H 9/02** (2006.01)

CPC (source: EP)  
**H01H 73/08** (2013.01); **H01H 9/0264** (2013.01); **H01H 2071/088** (2013.01)

Cited by  
DE19632726A1; AT399437B; AT404646B; FR2774506A1; ES2156536A1; GB2301940A; EP0748018A3; WO0129856A1

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0238960 A1 19870930; EP 0238960 B1 19920108**; AT E71473 T1 19920115; DE 3775800 D1 19920220

DOCDB simple family (application)  
**EP 87103747 A 19870314**; AT 87103747 T 19870314; DE 3775800 T 19870314