

Title (en)

DIFFERENTIAL TRANSCEIVER WITH LINE INTEGRITY DETECTION

Publication

EP 0239731 A3 19890308 (EN)

Application

EP 87100925 A 19870123

Priority

US 83567486 A 19860303

Abstract (en)

[origin: EP0239731A2] A differential transceiver transmission line integrity detector detects both open and short circuits in the transmission lines (12,14). The two transmission lines are terminated at both ends by selected impedances. A driver (30, 32) coupled to each of the transmission lines drives the lines with data signals. Signal levels on the lines are detected and compared with expected levels to generate line integrity indications. Both open and short conditions are detected and indicated by the line integrity indications.

IPC 1-7

H04L 25/08; **H04L 1/00**

IPC 8 full level

G01R 31/02 (2006.01); **H04L 25/08** (2006.01)

CPC (source: EP US)

H04L 25/085 (2013.01 - EP US)

Citation (search report)

- [X] DE 2335408 B1 19741212 - TELEFONBAU & NORMALZEIT GMBH
- [A] PATENT ABSTRACTS OF JAPAN, vol. 3, no. 5 (E-84)[144], 18th January 1979, page 144 E84; & JP-A-53 132 934 (MITSUBISHI DENKI K.K.) 20-11-1978

Cited by

EP0810446A3; FR2716060A1; US5696777A; EP0416679A1; US5124990A; AU640691B2; US6745342B1; WO0004684A1; WO0148994A1; WO9611541A3; WO9642159A1; WO9117615A3

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0239731 A2 19871007; **EP 0239731 A3 19890308**; **EP 0239731 B1 19921223**; DE 3783155 D1 19930204; DE 3783155 T2 19930701; JP H0565110 B2 19930917; JP S62206464 A 19870910; US 4782300 A 19881101

DOCDB simple family (application)

EP 87100925 A 19870123; DE 3783155 T 19870123; JP 922587 A 19870120; US 83567486 A 19860303