

Title (en)  
Input circuit.

Title (de)  
Eingangsschaltung.

Title (fr)  
Circuit d'entrée.

Publication  
**EP 0239939 A2 19871007 (EN)**

Application  
**EP 87104523 A 19870326**

Priority  
JP 7284386 A 19860331

Abstract (en)  
An input circuit is disclosed, which can be driven by a single power supply, and which can convert an ECL-level input signal falling to a negative voltage into a CMOS-level signal rising to a positive voltage, and can then supply this CMOS-level signal to an inner circuit. The input circuit comprises a transistor (13), a bias circuit (22, 23, 30-33), and a current-to-voltage converter (24). The emitter of the transistor (13) is coupled to an input terminal for receiving a signal of a negative potential. The bias circuit (22, 23, 30-33) applies a negative bias voltage to the base of the transistor (13). The current-to-voltage converter (24) is connected to the collector of the transistor (13). The converter (24) outputs a signal first falling to a positive level and then rising to another positive level. That is, the input circuit can convert an input signal of a negative level to a signal of a positive level.

IPC 1-7  
**H03K 19/092**; **H03K 19/094**

IPC 8 full level  
**H01L 27/02** (2006.01); **H03K 19/0175** (2006.01); **H03K 19/018** (2006.01); **H03K 19/0944** (2006.01)

CPC (source: EP KR US)  
**H03K 19/017518** (2013.01 - EP US); **H03K 19/09448** (2013.01 - EP KR US)

Cited by  
EP0313746A3; EP0395071B1

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**EP 0239939 A2 19871007**; **EP 0239939 A3 19881214**; **EP 0239939 B1 19920930**; DE 3781919 D1 19921105; DE 3781919 T2 19930218; JP S62230222 A 19871008; KR 870009478 A 19871027; KR 900004591 B1 19900630; US 4798981 A 19890117

DOCDB simple family (application)  
**EP 87104523 A 19870326**; DE 3781919 T 19870326; JP 7284386 A 19860331; KR 870003028 A 19870331; US 2838587 A 19870320