

Title (en)
SAFETY SKI BINDING

Publication
EP 0241360 B1 19890913 (FR)

Application
EP 87400734 A 19870403

Priority
FR 8604970 A 19860408

Abstract (en)
[origin: US4765641A] A resilient mechanism for maintaining the jaw unit of a safety ski binding in the normal boot-retaining position includes two vertical flat faces extending transversely on a stationary jaw-unit support. Two flat cams applied against the flat faces by a single spring consist respectively of a bearing surface of the jaw-unit body and of a small bearing plate carried by a rod on which the jaw-unit body is slidably mounted. The rod is slidably mounted within a knuckle-bearing orifice of the stationary support and is thus capable of pivotal displacement with the jaw unit in all directions on the stationary support.

IPC 1-7
A63C 9/085

IPC 8 full level
A63C 9/085 (2012.01); **A63C 9/00** (2012.01); **A63C 9/08** (2012.01)

CPC (source: EP US)
A63C 9/08542 (2013.01 - EP US); **A63C 9/0855** (2013.01 - EP US); **A63C 9/08564** (2013.01 - EP US); **A63C 9/001** (2013.01 - EP US); **A63C 9/0805** (2013.01 - EP US)

Cited by
AT403889B; FR2633191A1; FR2652273A2; US11491388B2; EP0352492A3; US5007657A; EP0856337A1; US8579317B2; EP3871743A1; FR3107652A1

Designated contracting state (EPC)
AT CH DE LI

DOCDB simple family (publication)
EP 0241360 A1 19871014; **EP 0241360 B1 19890913**; AT E46272 T1 19890915; DE 3760544 D1 19891019; FR 2596664 A1 19871009; FR 2596664 B1 19881223; JP 2761639 B2 19980604; JP S62243573 A 19871024; US 4765641 A 19880823

DOCDB simple family (application)
EP 87400734 A 19870403; AT 87400734 T 19870403; DE 3760544 T 19870403; FR 8604970 A 19860408; JP 8672987 A 19870408; US 3492187 A 19870406