

Title (en)
METHOD AND APPARATUS FOR COOLING A CONTINUOUSLY CAST METAL PRODUCT

Publication
EP 0241445 B1 19891011 (FR)

Application
EP 87870033 A 19870309

Priority
BE 648206 A 19860318

Abstract (en)
[origin: EP0241445A1] 1. Device for the cooling of a continuously cast metal product (1), which is composed of at least one box (4; 5) having a plane wall (6; 7) pierced with orifices (9; 10), called a front wall, and equipped with means (11; 12) for the supply of cooling fluid under pressure, each box being arranged in the secondary cooling zone of the said metal product (1), in such a way that its front wall is turned towards one face of the metal product at some distance from this, characterized in that the said front wall (6; 7) of the said boxes (4; 5) is inclined at an angle of between 0 degree and 1 degree relative to the transverse midplane of the metal product (1) to be cooled, in such a way that the distance between the said front wall (6; 7) and the corresponding face of the metal product increases in the direction of travel of the said product (1).

IPC 1-7
B22D 11/124

IPC 8 full level
B22D 11/124 (2006.01); **B22D 11/128** (2006.01)

CPC (source: EP US)
B22D 11/124 (2013.01 - EP US); **B22D 11/128** (2013.01 - EP US)

Cited by
EP0382702A3; EP0650790A1; US5634512A; CN1052435C

Designated contracting state (EPC)
AT DE ES FR GB IT LU NL SE

DOCDB simple family (publication)
EP 0241445 A1 19871014; EP 0241445 B1 19891011; AT E47061 T1 19891015; ES 2011824 B3 19900216; JP H0783918 B2 19950913; JP S62227562 A 19871006; US 4751960 A 19880621

DOCDB simple family (application)
EP 87870033 A 19870309; AT 87870033 T 19870309; ES 87870033 T 19870309; JP 6364487 A 19870318; US 2748087 A 19870318