

Title (en)
SWITCH DEVICE

Publication
EP 0242441 A3 19881012 (EN)

Application
EP 86116653 A 19861201

Priority
US 85444286 A 19860421

Abstract (en)
[origin: EP0242441A2] A switch device comprises a resilient contact member (2) and a support member (30) carrying the contact member. The support member is movable between a first position in which the contact member is in electrically-conductive contact with two conductor elements (10) that are stationary relative to each other and a second position in which the contact member is spaced from at least one of the conductor elements. A resilient member (36) urges the support member in the direction from the second position towards the first position.

IPC 1-7
H01H 19/62; H01H 1/24

IPC 8 full level
H01H 13/12 (2006.01); **H01H 1/40** (2006.01); **H01H 19/62** (2006.01); **H01H 11/00** (2006.01)

CPC (source: EP)
H01H 1/403 (2013.01); **H01H 19/626** (2013.01); **H01H 11/0056** (2013.01)

Citation (search report)
• [A] US 4559419 A 19851217 - OVERMAN DAVID L [US], et al
• [A] FR 2331891 A1 19770610 - TEKTRONIX INC [US]
• [AD] US 3719788 A 19730306 - HOLLAND K, et al

Cited by
EP0622818A3; GB2420448A; GB2420448B

Designated contracting state (EPC)
DE FR GB NL

DOCDB simple family (publication)
EP 0242441 A2 19871028; EP 0242441 A3 19881012; JP S62256324 A 19871109

DOCDB simple family (application)
EP 86116653 A 19861201; JP 9848087 A 19870421