

Title (en)  
ELECTRICAL CIRCUIT BREAKER

Publication  
**EP 0243648 B1 19900912 (DE)**

Application  
**EP 87103952 A 19870318**

Priority  
CH 135186 A 19860407

Abstract (en)  
[origin: US4816798A] An electrical protection switch, or circuit breaker, includes a movable contact part rotatably seated on a bolt which is secured to a leg of a mount. The other leg of the mount lies against a flange of a coil member which forms a portion of a magnetic release means. Two retaining elements extending parallel to one another and mutually spaced apart project from this flange. The retaining elements accept one leg of the mount therebetween and are provided with resilient tongues which press against the leg of the mount lying against the flange and, thus, press the leg against the flange. Fastening of the mount having the movable contact part to the magnetic release means, or coil member, is performed simply by slipping the mount onto the coil member by a snap-in connection.

IPC 1-7  
**H01H 71/24**; **H01H 73/18**

IPC 8 full level  
**H01H 71/24** (2006.01); **H01H 73/18** (2006.01); **H01H 73/36** (2006.01); **H01H 73/50** (2006.01); **H01H 71/02** (2006.01)

CPC (source: EP US)  
**H01H 71/2463** (2013.01 - EP US); **H01H 73/18** (2013.01 - EP US); **H01H 71/02** (2013.01 - EP US); **H01H 71/2454** (2013.01 - EP US); **H01H 71/2481** (2013.01 - EP US)

Cited by  
DE29802348U1; FR2779567A1; EP0335774A1; FR2629633A1; WO9963564A1; EP2544207B1

Designated contracting state (EPC)  
CH DE FR GB IT LI SE

DOCDB simple family (publication)  
**EP 0243648 A1 19871104**; **EP 0243648 B1 19900912**; CH 670170 A5 19890512; DE 3764854 D1 19901018; FI 84410 B 19910815; FI 84410 C 19911125; FI 871474 A0 19870403; FI 871474 A 19871008; JP 2522938 B2 19960807; JP S62243222 A 19871023; US 4816798 A 19890328

DOCDB simple family (application)  
**EP 87103952 A 19870318**; CH 135186 A 19860407; DE 3764854 T 19870318; FI 871474 A 19870403; JP 8561087 A 19870407; US 3260087 A 19870401