

Title (en)

Device for fastening an intermediate layer on a cylinder of a rotary printing machine.

Title (de)

Vorrichtung zum Festhalten von Zwischenlagen an Zylindern von Rotationsdruckmaschinen.

Title (fr)

Dispositif pour retenir une feuille intermédiaire sur un cylindre d'une machine à imprimer rotative.

Publication

EP 0243719 A2 19871104 (DE)

Application

EP 87104921 A 19870402

Priority

DE 3614541 A 19860429

Abstract (en)

[origin: US4854237A] To adhere an underlay in the clamping groove of a printing machine cylinder, for example a blanket cylinder of a rotary sheet offset printing machine, magnetic foil strips (7, 8, 23, 24, 33) are provided, clamping the end portion (6, 22, 32) of the underlay (4, 19, 30) either between two foil strips (FIGS. 1, 2) or against a magnetic portion within the groove, typically the inner side wall surface (9, 20, 34) defining the groove. The other end portion of the underlay can be left free, and will be clamped in position by stretching the rubber blanket or printing plate, respectively, over the cylinder.

Abstract (de)

An einem Platten oder Gummitücher tragenden Zylinder (2) einer Rotationsdruckmaschine wird eine als Teil des Aufzugs verwendete Zwischenlage (A) aus Papier oder Karton mittels einer aus Magnetfolienstreifen (7,8) bestehenden Vorrichtung an einem metallischen Teil des Spannkanaals (5) festgehalten.

IPC 1-7

B41F 27/02

IPC 8 full level

B41F 27/02 (2006.01); **B41F 30/00** (2006.01)

CPC (source: EP US)

B41F 27/02 (2013.01 - EP US)

Cited by

EP0786340A3; WO0187611A3

Designated contracting state (EPC)

CH DE FR IT LI SE

DOCDB simple family (publication)

EP 0243719 A2 19871104; EP 0243719 A3 19890419; DE 3614541 A1 19871105; JP S62261440 A 19871113; US 4854237 A 19890808

DOCDB simple family (application)

EP 87104921 A 19870402; DE 3614541 A 19860429; JP 10018787 A 19870424; US 3168787 A 19870327