

Title (en)

Safety device for a repeating rifle.

Title (de)

Vorrichtung zum Sichern von Repetierbüchsen.

Title (fr)

Dispositif de sécurité pour fusils à répétition.

Publication

EP 0243755 A2 19871104 (DE)

Application

EP 87105259 A 19870409

Priority

DE 3612386 A 19860412

Abstract (en)

A simple safety device for a repeating rifle which can also be provided at a later date, wherein a striker nut is guided in a lock and is connected to a striker guided in a closure, which striker is under the effect of a striker spring, and the striker nut can be arrested in a cocked position and, on release from the cocked position, the striker spring presses the striker against the percussion cap of a cartridge. A counter-bearing (5) of the striker spring (5a) is constructed so as to be axially displaceable, can be arrested in a position of readiness counter to the effect of the striker spring (5a) and can be brought from this position under the effect of the striker spring (5a) into a safety position. <IMAGE>

Abstract (de)

Die Erfindung sieht eine einfache, auch nachträglich vorzusehende Vorrichtung zum Sichern von Repetierbüchsen, wobei in einem Schlößchen eine Schlagbolzenmutter geführt ist, die mit einem in einem Verschluß geführten Schlagbolzen verbunden ist, der unter der Einwirkung einer Schlagfeder steht und wobei die Schlagbolzenmutter in einer Spannstellung arretierbar ist und bei Freigabe aus der Spannstellung die Schlagfeder den Schlagbolzen gegen das Zündhütchen einer Patrone drückt vor, die derart ausgestaltet ist, daß ein Gegenlager (5) der Spannfeder (5a) axial verschiebbar ausgebildet ist, in einer Bereitschaftsstellung entgegen der Wirkung der Schlagfeder (5a) arretierbar ist und aus dieser unter der Wirkung der Schlagfeder (5a) in eine Sicherheitsstellung bringbar ist.

IPC 1-7

F41C 17/04; F41C 19/14

IPC 8 full level

F41A 17/64 (2006.01); **F41A 19/34** (2006.01)

CPC (source: EP)

F41A 17/64 (2013.01); **F41A 19/34** (2013.01)

Cited by

EP1126230A1; US8112927B2; WO2008142520A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0243755 A2 19871104; EP 0243755 A3 19880107; DE 3612386 A1 19871015

DOCDB simple family (application)

EP 87105259 A 19870409; DE 3612386 A 19860412