Title (en)

PROTECTING DEVICE AGAINST DRILLING OF A LOCK

Publication

EP 0244564 B1 19890705 (DE)

Application

EP 87101566 A 19870205

Priority

- DE 8612668 U 19860509
- DE 8625816 U 19860926

Abstract (en)

[origin: EP0244564A1] 1. An anti-drilling protector for the actuating elements (7) of positioning bar fittings (1) for windows or doors or the like, the protector comprising a flat plate which is made of hardened steel or sintered steel or hard ceramic or the like and which is introducible on the outside of the actuating elements (7) into the mortice (14) in the door or window frame member (15), the edge contour of such plate being adapted to the contour of the mortice (14), the plate (17) being directly engageable on the outer lateral surface of the lock casing (6) and being adapted to bear by way of a longitudinal edge (18) on the back of the face plate (2) or a base part (19) of the lock casing (6), characterized in that stays (20, 22) project at right angles from the plate side surface near the actuating elements (7) or near the lock casing (6) receiving the same and have end parts (21) or a plate (23) respectively, a thin disc or a flat head, and the end parts (21) or plates (23) respectively, discs or heads of the stays (20, 22) engage behind bearing surfaces on the actuating elements (7) or casing (6) respectively.

IPC 1-7

E05B 17/20; E05C 21/02

IPC 8 full level

E05B 15/16 (2006.01); E05B 17/20 (2006.01); E05C 21/02 (2006.01)

CPC (source: EP)

E05B 15/1614 (2013.01)

Cited by

EP0632176A1; DE102012108371B4; DE102012108371B8; DE102012108371A1; DE202012012962U1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0244564 A1 19871111; EP 0244564 B1 19890705; DE 3760296 D1 19890810

DOCDB simple family (application)

EP 87101566 A 19870205; DE 3760296 T 19870205