

Title (en)  
COIN CHECKING APPARATUS

Publication  
**EP 0245805 B1 19920805 (DE)**

Application  
**EP 87106761 A 19870509**

Priority  
CH 196586 A 19860514

Abstract (en)  
[origin: US4815579A] Two sensors (2, 3) are placed opposite each other against the rim of the coin (5). By this, a signal, corresponding to the diameter of the coin (5) is produced and a drive (18/19, 23/24) is driven which moves two support members in order to support a coin between them (13), the diameter of which corresponds to the distance between the sensors (2, 3) in a position that is centered to a test coil (10) of an inductive coin testing device.

IPC 1-7  
**G07D 5/02**; **G07D 5/08**; **G07F 3/02**

IPC 8 full level  
**G07D 5/02** (2006.01); **G07D 5/08** (2006.01)

CPC (source: EP US)  
**G07D 5/02** (2013.01 - EP US); **G07D 5/08** (2013.01 - EP US)

Cited by  
EP0546341A1; EP0508560A3; DE4139503A1

Designated contracting state (EPC)  
AT DE FR GB IT NL SE

DOCDB simple family (publication)  
**EP 0245805 A2 19871119**; **EP 0245805 A3 19880921**; **EP 0245805 B1 19920805**; AT E79190 T1 19920815; CH 670717 A5 19890630; DE 3780858 D1 19920910; US 4815579 A 19890328

DOCDB simple family (application)  
**EP 87106761 A 19870509**; AT 87106761 T 19870509; CH 196586 A 19860514; DE 3780858 T 19870509; US 4950587 A 19870514