

Title (en)

WATCH CASE AND STRAP ASSEMBLY

Publication

EP 0246449 B1 19901024 (FR)

Application

EP 87105614 A 19870415

Priority

CH 187286 A 19860507

Abstract (en)

[origin: US4794577A] To avoid having to pierce them, which would be detrimental to their mechanical resistance to pull, the end portions (5, 6) of the wristlet are retained in slots (3, 4) provided in the watch-case middle (1) by pins (7, 8) partly accommodated in grooves (9, 10) formed in one surface of the slots (3, 4).

IPC 1-7

G04B 37/16

IPC 8 full level

A44C 5/14 (2006.01); **G04B 37/14** (2006.01)

CPC (source: EP KR US)

G04B 37/00 (2013.01 - KR); **G04B 37/1486** (2013.01 - EP US)

Cited by

DE20115025U1; DE3725960A1; EP2818942A1; EP2781973A1; US9342052B2

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0246449 A1 19871125; **EP 0246449 B1 19901024**; BR 8702209 A 19880217; CH 667770G A3 19881115; DE 3765693 D1 19901129;
JP S62268505 A 19871121; KR 870011516 A 19871224; US 4794577 A 19881227

DOCDB simple family (application)

EP 87105614 A 19870415; BR 8702209 A 19870504; CH 187286 A 19860507; DE 3765693 T 19870415; JP 10993787 A 19870507;
KR 870003260 A 19870406; US 3985787 A 19870420