

Title (en)

CONTAINER WITH RESEALABLE SEALING DEVICE.

Title (de)

MIT EINEM WIEDERVERSCHLIESSBAREN ABDICHTUNGSELEMENT VERSEHENER BEHÄLTER.

Title (fr)

RECIPIENT POURVU D'UN ELEMENT D'ETANCHEITE POUVANT ETRE REFERME.

Publication

EP 0247031 A4 19881208 (EN)

Application

EP 85905476 A 19851022

Priority

US 8502089 W 19851022

Abstract (en)

[origin: GB2189461A] A container (10) having an access opening (18) and a resealable sealing device (14), the latter consisting of a closure flap (16) which is secured at one end region (16a) to the front side of the container and is coated with a pressure-sensitive adhesive (28) to permit the container to be opened and resealed. A pair of L-shaped cuts (19a/19b) are formed in the flap to define a pair of tabs or fingers (16b) integral with the one end region of the flap, and a pair of tear prevention holes (20) are formed at the ends of the cuts on the line of attachment of the body of the flap to the one end region thereof, all to prevent the flap from tearing away from the container. In one embodiment of the invention, a non-adhesive member (24) is cut peninsularly out of the front side of the container to define the access opening and is adhesively secured to the coated face of the flap, and an additional pair of tear prevention holes (26) are provided in the non-adhesive member at the ends of its side edges on a second line of attachment coinciding with the first line of attachment.

IPC 1-7

B65D 33/16; **B65D 33/20**

IPC 8 full level

B65D 75/58 (2006.01); **B65D 75/20** (2006.01)

CPC (source: EP)

B65D 75/5838 (2013.01); **B65D 75/20** (2013.01); **B65D 2575/586** (2013.01)

Citation (search report)

See references of WO 8702645A1

Cited by

US5524759A

Designated contracting state (EPC)

BE FR IT

DOCDB simple family (publication)

GB 2189461 A 19871028; **GB 2189461 B 19891011**; **GB 8708624 D0 19870513**; EP 0247031 A1 19871202; EP 0247031 A4 19881208; EP 0247031 B1 19900328; WO 8702645 A1 19870507

DOCDB simple family (application)

GB 8708624 A 19851022; EP 85905476 A 19851022; US 8502089 W 19851022