

Title (en)

METHOD FOR PRE-TREATING A PRINTING SUPPORT STRIP

Publication

**EP 0247337 A3 19890329 (DE)**

Application

**EP 87105106 A 19870407**

Priority

DE 3618161 A 19860530

Abstract (en)

[origin: EP0247337A2] In order to avoid a differential distribution of moisture in the print support web after a planographic printing operation in which a damping liquid is added, a thin layer of a colourless, printable, water-repellent material, for example a silicone varnish, a UV varnish or an impregnating liquid is applied to the web before printing takes place.

IPC 1-7

**B41M 1/36**; B41M 1/30; B41M 1/06

IPC 8 full level

**B41M 5/52** (2006.01); **B41M 5/00** (2006.01)

CPC (source: EP)

**B41M 5/52** (2013.01); **B41M 5/5209** (2013.01); **B41M 5/529** (2013.01)

Citation (search report)

- [A] WO 8502133 A1 19850523 - ROBBART EDWARD
- [A] EP 0076905 A2 19830420 - BASF FARBEN & FASERN [DE]
- [A] DE 1944962 A1 19700319 - CARTIERE AMBROGIO BINDA SPA
- [A] FR 1264233 A 19610619 - ICI LTD
- [AD] DE 2457509 A1 19760610 - MASCHF AUGSBURG NUERNBERG AG
- [A] PATENT ABSTRACTS OF JAPAN, Band 7, Nr. 197 (M-239)[1342], 27. August 1983; & JP - A - 58 096 586 (YUUZOU KATOU) 08-06-1983

Designated contracting state (EPC)

CH DE FR IT LI SE

DOCDB simple family (publication)

**EP 0247337 A2 19871202**; **EP 0247337 A3 19890329**

DOCDB simple family (application)

**EP 87105106 A 19870407**