

Title (en)

METHOD AND APPARATUS FOR ENHANCING THE OPERATING CAPABILITIES OF A TELEPHONE SWITCHING SYSTEM

Publication

EP 0248190 A3 19900711 (EN)

Application

EP 87105839 A 19870421

Priority

US 86616586 A 19860522

Abstract (en)

[origin: EP0248190A2] A method and apparatus is described for providing extended subscriber features, e.g., equal access, to otherwise non-conforming central offices of a telephone switching system. According to the invention, a register module is interposed between the subscriber line and an input of the central office for intercepting digits from the subscriber line intended for the central office and for receiving subscriber information from the central office identifying the subscriber line. The register module includes a memory having a plurality of address locations and a control circuit for analyzing the intercepted digits to determine whether processing of the subscriber call requires an extended subscriber feature. If so, the intercepted digits are processed to generate a coded signal, the coded signal including the address location where the stored digits and the subscriber information resides in the memory. The coded signal is then used by the marker in the central office to select an appropriate outgoing trunk to complete the subscriber call. An associated trunk module interposed between the switch element of the central office and the outgoing trunks receives the coded signal and in response thereto polls the register module to request transmission of the digits and the subscriber information. Upon receipt of this data, the trunk module outputs a signal to the selected trunk.

IPC 1-7

H04Q 3/42; **H04Q 3/545**

IPC 8 full level

H04Q 3/42 (2006.01); **H04Q 3/66** (2006.01)

CPC (source: EP US)

H04Q 3/42 (2013.01 - EP US); **H04Q 3/665** (2013.01 - EP US)

Citation (search report)

- [A] US 4577066 A 19860318 - BIMONTE BRIAN R [US], et al
- [E] US 4685127 A 19870804 - MILLER ARTHUR O [US], et al
- IBM Technical Disclosure Bulletin, Vol. 28, No. 7, December 1985, pages 2816-2818, "Enhancement to crossbar switching systems", whole document.
- Proceedings of the Third International Conference on Computer Communication, August 3-6, 1976, pages 340-342, Toronto, CA; R.R. JUENEMAN et al.: "Explicit path routing in communications networks", page 340, left-hand column, lines 2-29; page 341, left-hand column, lines 27-35; page 341, right-hand column, line 20 - page 342, left-hand column, line 19.
- Bell Systems Technical Journal, Vol. 61, No. 7, September 1982, Part 3, pages 1599-1608, Murray Hill, New Jersey, US; R.F. FRERKING et al.: "Routing of direct-signaling messages in the CCIS network", page 1603, line 3 - page 1604, line 11; page 1605, lines 10-18; figures 1-3.
- IBM Technical Disclosure Bulletin, Vol. 26, No. 12, May 1984, pages 6438-6439, New York, US; B.L. HILLSBERG: "Determination of acceptable message paths through a multi-node communication network", whole document.

Cited by

EP0339127A3; EP0430534A1; ES2105934A1; AU618897B2; EP0898432A1; US6195427B1; WO9909758A1; WO9604758A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0248190 A2 19871209; **EP 0248190 A3 19900711**; CA 1273090 A 19900821; US 4782519 A 19881101

DOCDB simple family (application)

EP 87105839 A 19870421; CA 536992 A 19870513; US 86616586 A 19860522