

Title (en)

METHOD AND DEVICE FOR CONTROLLING A STEPPER MOTOR

Publication

EP 0250862 B1 19891129 (FR)

Application

EP 87107571 A 19870525

Priority

CH 258586 A 19860626

Abstract (en)

[origin: US4754210A] The method and the device described are intended to avoid the dissipation of electrical energy that occurs in the coil of a stepping motor when the coil is short-circuited permanently between two drive pulses. The method comprises short-circuiting the coil at the end (t1) of the drive pulse, then putting it on open circuit at the instant (t2) when the current (Ic) flowing through it during the short-circuit becomes zero, and short-circuiting the coil again at the instant (t3) when the voltage induced in it by the rotation of the rotor while the coil is on open circuit becomes zero or reaches a predetermined value (Ud). The device is designed to carry out the method. The invention is applicable to the control of stepping motors of the type for instance that are fitted in electronic timepieces having a hand display.

IPC 1-7

G04C 3/14

IPC 8 full level

H02P 8/02 (2006.01); **G04C 3/14** (2006.01)

CPC (source: EP US)

G04C 3/14 (2013.01 - EP US)

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0250862 A1 19880107; **EP 0250862 B1 19891129**; CH 665084G A3 19880429; DE 3761064 D1 19900104; JP 2655645 B2 19970924; JP S637199 A 19880113; US 4754210 A 19880628

DOCDB simple family (application)

EP 87107571 A 19870525; CH 258586 A 19860626; DE 3761064 T 19870525; JP 15670087 A 19870625; US 5320187 A 19870522