

Title (en)
LUBRICANT FOR METAL FORMATION

Publication
EP 0251192 A3 19880504 (DE)

Application
EP 87109098 A 19870624

Priority
JP 15117886 A 19860627

Abstract (en)
[origin: EP0251192A2] The aqueous lubricant for metal cold-forming contains 10 to 35% by weight of a thermosetting acrylate-based resin having a glass transition point of -10 to +25 DEG C, 3 to 15% by weight of wax and 0.5 to 5% by weight of a surfactant, the thermosetting resin/wax weight ratio being adjusted to 2-12. Particularly suitable resins are of the general formula $-(Ra-Rb-Rc-Rd)_n-$, Ra, Rb, Rc and Rd being different monomers and "n" being a degree of polymerisation from 1,000 to 50,000. The wax should have a melting point above 45 DEG C. In the process for facilitating the cold-forming of metallic workpieces, the lubricant is applied to the metal surface, dried on in air to form a coating weight from 0.5 to 30 g/m², heated to a temperature of 80 to 120 DEG C (object temperature) and finally cured.

IPC 1-7
C10M 173/02

IPC 8 full level
C10M 173/02 (2006.01); **C10N 40/24** (2006.01); **C10N 50/02** (2006.01)

CPC (source: EP)
C10M 143/02 (2013.01); **C10M 143/10** (2013.01); **C10M 145/14** (2013.01); **C10M 145/16** (2013.01); **C10M 149/06** (2013.01); **C10M 149/08** (2013.01); **C10M 153/04** (2013.01); **C10M 159/06** (2013.01); **C10M 173/02** (2013.01); **C10M 2201/00** (2013.01); **C10M 2201/02** (2013.01); **C10M 2201/041** (2013.01); **C10M 2201/042** (2013.01); **C10M 2201/061** (2013.01); **C10M 2201/062** (2013.01); **C10M 2201/066** (2013.01); **C10M 2201/105** (2013.01); **C10M 2201/16** (2013.01); **C10M 2201/18** (2013.01); **C10M 2205/022** (2013.01); **C10M 2205/04** (2013.01); **C10M 2205/14** (2013.01); **C10M 2205/16** (2013.01); **C10M 2205/17** (2013.01); **C10M 2207/021** (2013.01); **C10M 2207/125** (2013.01); **C10M 2207/129** (2013.01); **C10M 2207/281** (2013.01); **C10M 2207/282** (2013.01); **C10M 2207/283** (2013.01); **C10M 2207/286** (2013.01); **C10M 2207/40** (2013.01); **C10M 2207/404** (2013.01); **C10M 2209/084** (2013.01); **C10M 2209/086** (2013.01); **C10M 2209/104** (2013.01); **C10M 2211/06** (2013.01); **C10M 2213/02** (2013.01); **C10M 2213/062** (2013.01); **C10M 2215/04** (2013.01); **C10M 2215/08** (2013.01); **C10M 2215/082** (2013.01); **C10M 2215/26** (2013.01); **C10M 2215/28** (2013.01); **C10M 2217/024** (2013.01); **C10M 2217/026** (2013.01); **C10M 2217/06** (2013.01); **C10M 2219/044** (2013.01); **C10M 2225/00** (2013.01); **C10M 2225/02** (2013.01); **C10M 2225/04** (2013.01); **C10M 2225/041** (2013.01); **C10N 2010/04** (2013.01); **C10N 2050/01** (2020.05); **C10N 2050/02** (2013.01)

Citation (search report)
• [Y] EP 0043182 A1 19820106 - USS ENG & CONSULT [US]
• [A] FR 2571381 A1 19860411 - NIPPON KOKAN KK [JP], et al
• [A] DE 3223442 A1 19830120 - EM LUBRICANTS INC [US]
• [A] DE 2529892 A1 19760129 - NIPPON PAINT CO LTD
• [Y] EP 0175547 A2 19860326 - NIPPON KOUSAKUYU CO LTD [JP]

Cited by
EP0398153A1; US8864916B2; CN110144255A; EP0718396A1; US6034041A; US6899770B1; US7696136B2; WO9216603A1

Designated contracting state (EPC)
AT BE CH DE FR IT LI NL SE

DOCDB simple family (publication)
EP 0251192 A2 19880107; EP 0251192 A3 19880504; EP 0251192 B1 19920506; AT E75770 T1 19920515; DE 3720841 A1 19880114; DE 3778764 D1 19920611; JP H0437878 B2 19920622; JP S638489 A 19880114

DOCDB simple family (application)
EP 87109098 A 19870624; AT 87109098 T 19870624; DE 3720841 A 19870624; DE 3778764 T 19870624; JP 15117886 A 19860627