

Title (en)
ADJUSTABLE STRIKER, AND TAMPER-PROOF MOUNTING MEANS

Publication
EP 0252781 A3 19880504 (FR)

Application
EP 87401272 A 19870605

Priority
• FR 8608176 A 19860606
• FR 8702120 A 19870219

Abstract (en)
[origin: EP0252781A2] The method of mounting involves the use of a striker which can be adjusted by compression springs. The opening (15) of the striker is adapted to receive the lock bolt and is defined between a force plate (9) and a mounting plate (1) used for attachment to the jamb (2). The screws used to attach the mounting plate (1) to the jamb (2) are metal screws (4, 4', 4'') which engage with threaded inserts (25, 18, 18') fixed securely into or onto the jamb (2). The inactive part of the lock bolt (36b) engages with the striker and is flanged by a clamp (41) which is adjustable in height. The locking of the "knurled" screws makes it possible, from the inside, to make the lock inoperative by blocking the bolt. <IMAGE>

IPC 1-7
E05B 15/02; **E05B 45/08**

IPC 8 full level
E05B 15/02 (2006.01); **E05B 45/08** (2006.01); **E05B 47/04** (2006.01)

CPC (source: EP)
E05B 15/0205 (2013.01); **E05B 15/024** (2013.01); **E05B 45/086** (2013.01)

Citation (search report)
• [X] US 3469877 A 19690930 - HUTCHISON CHARLES H
• [Y] DE 1185948 B 19650121 - CURT WEINERT
• [Y] US 2660632 A 19531124 - KENJI MAKISHIMA
• [A] FR 2516969 A1 19830527 - DORILLE JEAN PIERRE [FR]

Cited by
GB2233025A; GB2292177A; GB2292177B; GB2220977A; GB2220977B; GB2280708A; GB2280708B; DE4317564A1; WO2009125436A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0252781 A2 19880113; **EP 0252781 A3 19880504**

DOCDB simple family (application)
EP 87401272 A 19870605