

Title (en)

METHOD AT THE MANUFACTURE OF MECHANICAL PULP

Publication

**EP 0252915 B1 19910206 (EN)**

Application

**EP 86902922 A 19860408**

Priority

SE 8502211 A 19850506

Abstract (en)

[origin: WO8606770A1] The refiner process and the properties of the pulp produced are controlled by means of an accelerometer positioned on a refiner disc, which accelerometer measures high-frequency vibrations. The signal from the accelerometer is converted to vibration energy, which is utilized together with one or several other process variables for controlling and adjusting the process.

IPC 1-7

**B02C 7/14; D21D 1/30**

IPC 8 full level

**B02C 7/14** (2006.01); **D21B 1/14** (2006.01); **D21D 1/00** (2006.01); **D21D 1/30** (2006.01)

CPC (source: EP)

**D21D 1/002** (2013.01); **D21D 1/30** (2013.01)

Designated contracting state (EPC)

AT DE FR GB SE

DOCDB simple family (publication)

**WO 8606770 A1 19861120**; AU 5863286 A 19861204; AU 599914 B2 19900802; CA 1281571 C 19910319; EP 0252915 A1 19880120;  
EP 0252915 B1 19910206; FI 874879 A0 19871104; FI 874879 A 19871104; JP S62502759 A 19871022; NZ 216017 A 19890127;  
SE 454189 B 19880411; SE 8502211 D0 19850506; SE 8502211 L 19861107

DOCDB simple family (application)

**SE 8600160 W 19860408**; AU 5863286 A 19860408; CA 508544 A 19860506; EP 86902922 A 19860408; FI 874879 A 19871104;  
JP 50268686 A 19860408; NZ 21601786 A 19860501; SE 8502211 A 19850506