

Title (en)

MANUAL CLAMP DEVICE FOR ATTACHMENT TO MACHINE TABLES, DEVICES ETC

Publication

EP 0252933 B1 19900725 (DE)

Application

EP 87900134 A 19861219

Priority

- DE 3600010 A 19860102
- DE 3640869 A 19861129

Abstract (en)

[origin: WO8704103A1] For clamping a workpiece (31) to a support surface (32) of, for example, a device plate (15), a manual clamp device with a clamping element (1) and a support element (3) is used, said support element being provided with a top portion (3a) and a support portion, in particular in the form of a threaded bolt (3b). The clamping element (1) is so located in an opening (2) of the top portion (3a), said opening being roughly parallel to the top surface (31a) of the workpiece, that it can effect pivoting and sliding movements and can largely fill the opening in the region of its greatest height. At the contact point (4) the clamping element (1) is convexly supported in the opening (2), presses at the clamping point (19) with its clamping lug (5) on the workpiece (31) and is pivoted counter-clockwise by a clamping screw (8) engaging in its rear end. To guide the clamping element (1) a guide element roughly in the form of a rod-shaped spring is provided, which is supported below on the threaded bolt (3b), engages in a longitudinal slot (12) of the clamping element (1) and the upper end of which forms, as applicable, an elastic stop (56) in relation to the workpiece (31). This device, composed of few parts, is designed to be extremely compact and simple and can be used in many applications in view of its large power transfer capacity.

IPC 1-7

B25B 5/10

IPC 8 full level

B25B 5/10 (2006.01)

CPC (source: EP)

B25B 5/108 (2013.01)

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

WO 8704103 A1 19870716; AT E54860 T1 19900815; DE 3673014 D1 19900830; EP 0252933 A1 19880120; EP 0252933 B1 19900725

DOCDB simple family (application)

EP 8600765 W 19861219; AT 87900134 T 19861219; DE 3673014 T 19861219; EP 87900134 A 19861219