

Title (en)  
DEVICE FOR WEFT INSERTION IN A GRIPPER LOOM

Publication  
**EP 0253184 B1 19900919 (DE)**

Application  
**EP 87109282 A 19870627**

Priority  
CH 282486 A 19860715

Abstract (en)  
[origin: US4771815A] The apparatus contains a ribbon wheel driven in alternating direction of rotation with a flexible insertion ribbon being wound and unwound in a first looping region of the ribbon wheel and lappable over more than 360 DEG of the circumference. A ribbon type guide element loops the portion of the insertion ribbon present on the ribbon wheel. The insertion ribbon and the guide element are each fastened at one end in a trough-like depression of the ribbon wheel by a recessed clamp which has a support surface adapted to the adjacent surface portions to be lapped and ascending in a circumferential direction in a continuous arc. The other end of the guide element is fastened by a second clamp disposed in the same or another depression.

IPC 1-7  
**D03D 47/12**

IPC 8 full level  
**D03D 47/12** (2006.01); **D03D 47/27** (2006.01)

CPC (source: EP US)  
**D03D 47/272** (2013.01 - EP US); **D03D 47/276** (2013.01 - EP US); **D03D 47/277** (2013.01 - EP US)

Cited by  
EP0726341A3; CH679937A5; EP0331801A1; FR2654119A1; BE1004172A3; EP0352223A1; US5035268A

Designated contracting state (EPC)  
BE DE FR IT

DOCDB simple family (publication)  
**EP 0253184 A1 19880120; EP 0253184 B1 19900919**; BR 8703659 A 19880322; DE 3765039 D1 19901025; JP S6328943 A 19880206; SU 1748654 A3 19920715; US 4771815 A 19880920

DOCDB simple family (application)  
**EP 87109282 A 19870627**; BR 8703659 A 19870714; DE 3765039 T 19870627; JP 11569987 A 19870512; SU 4202817 A 19870626; US 6889487 A 19870630