

Title (en)  
PATTERN FORMING SATURATOR AND METHOD

Publication  
**EP 0253565 B1 19891115 (EN)**

Application  
**EP 87306042 A 19870708**

Priority  
US 88355086 A 19860709

Abstract (en)  
[origin: EP0253565A1] A saturator of the type comprising a chamber (18) situated between a chamber defining element (16) and a mandrel (12), in which a web (40) is moved between the chamber defining element and the mandrel to impregnate the web with a saturant contained in the chamber includes a stencil (50) having at least one impermeable region (52) shaped to cover less than the entire web. The stencil is passed through the chamber at the same speed as the web with the stencil juxtaposed against the web such that portions of the web aligned with the at least one impermeable region are not impregnated with the saturant, while other exposed portions of the web are impregnated with the saturant.

IPC 1-7  
**B05C 3/20**; **D06B 11/00**; **D21H 5/06**

IPC 8 full level  
**B05C 3/10** (2006.01); **B05C 3/18** (2006.01); **B05C 3/20** (2006.01); **B05D 5/00** (2006.01); **B29B 15/10** (2006.01); **D06B 11/00** (2006.01); **D21H 19/38** (2006.01); **D21H 21/34** (2006.01); **D21H 23/00** (2006.01); **D21H 23/22** (2006.01)

CPC (source: EP US)  
**D06B 11/0089** (2013.01 - EP US); **D21H 5/0015** (2013.01 - EP US); **D21H 23/40** (2013.01 - EP US)

Cited by  
DE29501918U1; GB2308852A; GB2308852B

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0253565 A1 19880120**; **EP 0253565 B1 19891115**; AT E47971 T1 19891215; AU 587557 B2 19890817; AU 7531487 A 19880114; CA 1258205 A 19890808; DE 3760981 D1 19891221; JP H0830318 B2 19960327; JP S6392792 A 19880423; US 4702943 A 19871027

DOCDB simple family (application)  
**EP 87306042 A 19870708**; AT 87306042 T 19870708; AU 7531487 A 19870707; CA 541572 A 19870708; DE 3760981 T 19870708; JP 17203487 A 19870709; US 88355086 A 19860709