

Title (en)
THREADED COUPLING FOR PERCUSSION DRILL RODS

Publication
EP 0253789 B1 19921119 (EN)

Application
EP 87850221 A 19870707

Priority
SE 8603118 A 19860715

Abstract (en)
[origin: EP0253789A2] The present invention refers to a threaded coupling for percussion drill rods having a diameter of 30 - 40 mm, comprising an external rod thread and an internal sleeve thread, the longitudinal section of said threads having continuously curved tops and bottoms. In threads of the type mentioned above it is desirable to be able to tighten them to a relatively high degree because otherwise the thread coupling loosens when used in hydraulic percussive drilling machines of a high frequency. Significant for the thread coupling of the present invention is that the pitch (S) is 7 - 11 mm, the radii of curvature (R1 - R4), at least for the portions of the tops and bottoms located immediately adjacent the contact shoulder, are 3 - 5 mm, and that the threads have a height (H1,H2) of 1.2 - 1.6 mm.

IPC 1-7
E21B 17/042; **F16L 15/00**

IPC 8 full level
F16D 1/06 (2006.01); **E21B 17/042** (2006.01); **F16B 33/04** (2006.01); **F16L 15/00** (2006.01)

CPC (source: EP US)
E21B 17/0426 (2013.01 - EP US); **Y10T 403/5746** (2015.01 - EP US)

Cited by
GB2410304A; WO2022180226A3; EP3536893A1; WO2019170437A1

Designated contracting state (EPC)
AT DE GB SE

DOCDB simple family (publication)
EP 0253789 A2 19880120; **EP 0253789 A3 19890322**; **EP 0253789 B1 19921119**; AT E82615 T1 19921215; CA 1291880 C 19911112; DE 3782688 D1 19921224; DE 3782688 T2 19930401; FI 86664 B 19920615; FI 86664 C 19920925; FI 873102 A0 19870713; FI 873102 A 19880116; IE 60576 B1 19940727; IE 871894 L 19880115; JP S6367418 A 19880326; SE 460550 B 19891023; SE 8603118 D0 19860715; SE 8603118 L 19880116; US 4861209 A 19890829; ZA 874990 B 19880114

DOCDB simple family (application)
EP 87850221 A 19870707; AT 87850221 T 19870707; CA 541944 A 19870714; DE 3782688 T 19870707; FI 873102 A 19870713; IE 189487 A 19870714; JP 17402087 A 19870714; SE 8603118 A 19860715; US 7380187 A 19870714; ZA 874990 A 19870708