

Title (en)
PULLEY

Publication
EP 0253808 B1 19881005 (DE)

Application
EP 86901294 A 19860221

Priority
AT 56785 A 19850226

Abstract (en)
[origin: WO8604885A1] The pulley (1) comprises a wheel (4) around which a cable (5) is wound. The wheel (4) is retained by a locking device (6). When the locking device (6) is released, the cable is unwound since a weight (14) is suspended at its ends (15). The cable (5) is so arranged that both its ends (15) are situated on one side of the wheel (4) when the cable is wound while they hang on either side of the wheel (4) when the cable (5) is unwound.

IPC 1-7
B66D 3/10; **A62B 1/10**; **A62B 1/02**

IPC 8 full level
A62B 1/06 (2006.01); **A62B 1/02** (2006.01); **A62B 1/10** (2006.01); **B66D 3/00** (2006.01); **B66D 3/10** (2006.01)

CPC (source: EP US)
A62B 1/02 (2013.01 - EP US); **A62B 1/10** (2013.01 - EP US); **B66D 3/10** (2013.01 - EP US)

Citation (examination)

- FR 2168717 A5 19730831 - RAGO JOHN [FR]
- GB 15346 A

Designated contracting state (EPC)
AT CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
WO 8604885 A1 19860828; AT E37700 T1 19881015; AU 5457786 A 19860910; AU 585952 B2 19890629; BR 8607064 A 19880223; CA 1260921 A 19890926; DE 3660863 D1 19881110; EP 0253808 A1 19880127; EP 0253808 B1 19881005; ES 296681 U 19881216; ES 296681 Y 19890701; JP S62501891 A 19870730; US 4767101 A 19880830; ZA 861396 B 19861029

DOCDB simple family (application)
AT 8600015 W 19860221; AT 86901294 T 19860221; AU 5457786 A 19860221; BR 8607064 A 19860221; CA 502672 A 19860225; DE 3660863 T 19860221; EP 86901294 A 19860221; ES 296681 U 19860225; JP 50134086 A 19860221; US 92822386 A 19861027; ZA 861396 A 19860225