

Title (en)

ADJUSTING DEVICE FOR A CAMSHAFT FOR CONTROLLING THE GAS INLET AND EXHAUST VALVES OF AN INTERNAL-COMBUSTION ENGINE

Publication

EP 0254058 A3 19890809 (DE)

Application

EP 87109060 A 19870624

Priority

DE 3624827 A 19860723

Abstract (en)

[origin: EP0254058A2] In an internal-combustion engine, in order to be able to vary the control times for opening and closing the gas inlet and outlet valves, the camshaft controlling the valves is constructed of two assemblies moving with respect to one another. A first assembly, supported on the internal-combustion engine, consists of a hollow outer shaft (1) with a first half of the control cams (5), for only the gas inlet or outlet valves, fixed thereto. The second assembly is an inner shaft (3), supported concentrically in the outer shaft (1), on which is mounted the second half of the control cams (4) via pins (7) protruding through radial slots in the outer shaft (1). The control cams (4) connected fixedly to the inner shaft (3) are supported on the outer shaft (1) such that they can rotate. By means of an adjusting device (10) integrated into the drive wheel (gear wheel 13), the angular position between the two halves of the control cams (4, 5) can be continuously adjusted over a predetermined range. The adjusting device (10) may be operated hydraulically or by means of an electrical stepping motor. The control signals for the adjusting device (10) are derived from selected engine operating data and namely, in particular, the air induction flow rate. <IMAGE>

IPC 1-7

F01L 1/34; **F16H 35/08**

IPC 8 full level

F01L 1/34 (2006.01); **F01L 1/344** (2006.01); **F16H 35/08** (2006.01)

CPC (source: EP)

F01L 1/34413 (2013.01); **F01L 2001/0473** (2013.01)

Citation (search report)

- [A] DE 3204841 A1 19830818 - VOLKSWAGENWERK AG [DE]
- [A] DE 446744 C 19270711 - SIEMENS SCHUCKERTWERKE GMBH
- [A] FR 593322 A 19250820
- [A] GB 191500889 A 19151230 - VALOBRA FERRUCCIO [IT]
- [A] FR 2426152 A1 19791214 - VOLKSWAGENWERK AG [DE]
- [A] US 1957181 A 19340501 - MITCHEL EDWARD W
- [A] US 3516394 A 19700623 - NICHOLS ROY G
- [A] DE 144450 C
- [A] US 1527456 A 19250224 - EDWARD WOYDT, et al
- [A] GB 154543 A 19211229 - LOUIS DAMBLANC
- [A] DE 254135 C 19121123 - RUTHARDT & CO [DE]
- [A] EP 0163046 A1 19851204 - PIERBURG GMBH & CO KG [DE]
- PATENT ABSTRACTS OF JAPAN, Band 9, Nr. 275 (M-246)(1998), 2. November 1985; & JP,A,60 119 309 (SUZUKI JIDOSHA KOGYO K.K.) 26-05-1985, Zusammenfassung; Figur.

Cited by

DE102014112464A1; US8225762B2; EP1043482A3; CN102197199A; CN105940191A; US6129061A; EP0918142A3; DE4110195C2; JP2014509711A; EP3176392A1; CN106837452A; JP2007533906A; DE3921923A1; FR3109797A1; GB2424258A; GB2424258B; EP1726789A1; EP0686754A3; US8584634B2; FR2843997A1; US6328006B1; US8651076B2; US10465569B2; FR2649443A1; JPH03111607A; US5165303A; US5577420A; WO2006050686A1; WO2007007168A1; WO2010054915A1; WO2015078588A1; WO2018206192A1; DE102016217860A1; WO2018050364A1; US7377243B2; US7588006B2; US8186319B2; US8893678B2; EP0367192B1; DE102011120815A1; WO2013083789A1; US9316127B2; US9926815B2; WO2005103455A1; WO2007052075A1; EP2920435B1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0254058 A2 19880127; **EP 0254058 A3 19890809**; **EP 0254058 B1 19920916**; DE 3624827 A1 19880204; DE 3781736 D1 19921022

DOCDB simple family (application)

EP 87109060 A 19870624; DE 3624827 A 19860723; DE 3781736 T 19870624