

Title (en)

SUPPORTING OR TENSION CABLE WITH A SHEATH, AND METHOD AND APPARATUS FOR MANUFACTURING SUCH A CABLE

Publication

EP 0255573 B1 19900718 (DE)

Application

EP 87106168 A 19870428

Priority

DE 3626886 A 19860808

Abstract (en)

[origin: US4821501A] A suspension cable is encased in a metal pipe formed from a metal strip wound in a series of adjacent helical windings on the cable. The longitudinal edges of adjacent windings are connected by a continuous tight fold.

IPC 1-7

D07B 1/16; **D07B 7/14**; **E01D 11/00**

IPC 8 full level

B65H 81/08 (2006.01); **D07B 1/16** (2006.01); **D07B 7/14** (2006.01); **E01D 11/00** (2006.01); **E01D 19/16** (2006.01)

CPC (source: EP US)

D07B 7/14 (2013.01 - EP US); **E01D 19/16** (2013.01 - EP US); **D07B 2201/2089** (2013.01 - EP US); **D07B 2201/2092** (2013.01 - EP US); **Y10T 29/5185** (2015.01 - EP US)

Cited by

EP0290749A3; CN108584498A

Designated contracting state (EPC)

DE ES FR GB GR IT NL

DOCDB simple family (publication)

EP 0255573 A1 19880210; **EP 0255573 B1 19900718**; DE 3626886 A1 19880211; DE 3763776 D1 19900823; ES 2017664 B3 19910301; GR 3000935 T3 19911210; JP S6342986 A 19880224; US 4821501 A 19890418; US 4894981 A 19900123

DOCDB simple family (application)

EP 87106168 A 19870428; DE 3626886 A 19860808; DE 3763776 T 19870428; ES 87106168 T 19870428; GR 900400768 T 19901012; JP 14619887 A 19870611; US 27879388 A 19881202; US 7672287 A 19870723