

Title (en)
GLAZING SYSTEM FOR GLASS-FRONTED BUILDINGS

Publication
EP 0255808 B1 19910306 (EN)

Application
EP 87830274 A 19870716

Priority
IT 347586 A 19860801

Abstract (en)
[origin: EP0255808A1] In the glazing system disclosed, each of the single lights (1) comprises an external window pane (15) and an internal window pane (24), and is surrounded by a frame (32) with a peripheral seal (18) that makes contact with a frontal seal (8) offered by and concealing the outermost surface of the skeleton framework (31); the internal window pane (24) can be opened independently of the external pane (15). Each frame (32) is fitted with an upwardly-directed hollow element (30) of length sufficient to ensure that rain and damp will be prevented from reaching the space between the internal and the external panes, however strong the wind may happen to be.

IPC 1-7
E04B 2/96

IPC 8 full level
E04B 2/96 (2006.01); **E06B 3/26** (2006.01); **E06B 3/54** (2006.01)

CPC (source: EP)
E04B 2/96 (2013.01); **E06B 3/2605** (2013.01); **E06B 3/5427** (2013.01); **E06B 2003/2615** (2013.01)

Cited by
KR101294361B1; EP0431230A1; EP0301462A1; WO9107563A3

Designated contracting state (EPC)
AT BE CH DE FR GR LI LU NL SE

DOCDB simple family (publication)
EP 0255808 A1 19880210; **EP 0255808 B1 19910306**; AT E61436 T1 19910315; DE 3768365 D1 19910411; GB 2193245 A 19880203; GB 2193245 B 19900425; GB 8702370 D0 19870311; IT 1200185 B 19890105; IT 8603475 A0 19860801

DOCDB simple family (application)
EP 87830274 A 19870716; AT 87830274 T 19870716; DE 3768365 T 19870716; GB 8702370 A 19870203; IT 347586 A 19860801